

SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

EPONTM Resin 1007F

Section 1. Product and company identification

GHS product identifier : EPONTM Resin 1007F

MSDS Number : K1978
Product type : Epoxy Resin

Material uses : Epoxy Resin Systems

Manufacturer/Supplier/Impor : Hexion Inc.

er 180 East Broad Street Columbus, Ohio

43215 USA

Contact person : 4information@hexion.com

Telephone : For additional health and safety or regulatory information, call

1 888 443 9466.

Emergency telephone number : For Emergency Medical Assistance

Call Health & Safety Information Services

1-866-303-6949

For Emergency Transportation Information CHEMTREC US Domestic (800) 424-9300 CHEMTREC International (703) 527-3887 CANUTEC CA Domestic (613) 996-6666

Section 2. Hazards identification

Classification of the substance or

mixture

: SKIN SENSITISATION - Category 1 REPRODUCTIVE TOXICITY - Category 2

COMBUSTIBLE DUSTS

GHS label elements

Hazard pictograms :

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H361f Suspected of damaging fertility.

May form combustible dust concentrations in air.

Precautionary statements

EPONTM Resin 1007F Page: 2/16

General : Not applicable.

Prevention : Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Use personal protective equipment as required.

Wear protective gloves. Avoid breathing dust.

Contaminated work clothing should not be allowed out of the

workplace.

Response : IF exposed or concerned:

Get medical attention.

IF ON SKIN:

Wash with plenty of soap and water. Wash contaminated clothing before reuse.

If skin irritation or rash occurs:

Get medical attention.

Storage : Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Other hazards which do not result in classification

Combustible dust when finely divided and suspended in air. Fine dust clouds may form explosive mixtures with air. Product can explode if

dust cloud is formed and ignited.

Minimize airborne dust. Eliminate all fire/ignition sources including static discharges near product/package. Prevent dust accumulation. Refer to Handling Section 7 of the MSDS for more information.

Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS
		number
4,4'-Isopropylidenediphenol	0.1 - 0.2	80-05-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the

EPONTM Resin 1007F Page:3/16

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

Protection of first aid personnel

: No specific treatment.

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media

- Use water spray or mist, dry chemical, foam or CO2.
- Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

- : Combustible solid that burns. Fine dust clouds may form explosive mixtures with air.
- Decomposition products may include the following materials: carbon oxides aldehydes acids

EPONTM Resin 1007F Page:4/16

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

For non-emergency personnel

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Minimize airborne dust and eliminate all fire/ignition sources. Clean up spill as soon as possible using procedures described below. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

Move containers from spill area. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor. Move containers from spill area. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid creating dusty conditions and prevent wind dispersal. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid creating dusty conditions and prevent wind dispersal. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces

EPONTM Resin 1007F Page: 5/16

and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

COMBUSTIBLE DUST HANDLING PROCEDURES:

Combustible dusts at sufficient concentrations can form explosive mixtures with air. High dust concentrations should be avoided. Follow US NFPA Standard 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids," UK HSE Guidance HSG 103, approved Codes of Practice (ACOPS) established for Explosive Atmospheres under the ATEX Directive 1999/92/EC for worker protection and ATEX Directive 94/9/EC that regulates equipment and protection systems used in potentially explosive atmospheres or other national guidance on safe handling of combustible dusts. Train workers in the recognition and prevention of hazards associated with combustible dust in the plant.

Minimize airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. Use continuous suction at points of dust generation to capture and minimize the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimize the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.

Control sources of static electricity. This product or the package itself

EPONTM Resin 1007F Page:6/16

can accumulate static charges, and static discharge can be a source of ignition. Solids handling systems must be designed in accordance with applicable NFPA standards (including 654 and 77) and other national guidance. Do not empty directly into flammable solvents or in the presence of flammable vapors. The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep away from heat, hot surfaces, sparks and flame. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	None.
4,4'-Isopropylidenediphenol	None.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or

EPONTM Resin 1007F Page:7/16

engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eve/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., For PPE selection see National Fire Protection Association (NFPA) 2113, Standard on Selection, Care, Use and Maintenance of Flame-Resistant Garments for Protection of Industrial Personnel Against Flash Fire.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Flakes.

Color : White to yellowish.

Odor : Not available
Odor threshold : Not available
pH : Not available

EPONTM Resin 1007F Page: 8/16

Melting point/ Freezing point : $120 - 130 \,^{\circ}\text{C} \, (248 - 266 \,^{\circ}\text{F})$

Boiling point : Not available

Flash point : Not defined for solids

Burning time:Not availableBurning rate:Not availableEvaporation rate:Not availableFlammability (solid, gas):Not available

Lower and upper explosive : **Lower:** Not defined for solids (See MEC)

(flammable) limits Upper: Not defined for solids

Vapor pressure : Not available Vapor density : Not available

Relative density : 1.19

Solubility : Not available Solubility in water : Negligible

Partition coefficient: n- Not available

octanol/water

Auto-ignition temperature: Not availableDecomposition temperature: Not availableSADT: Not available

Viscosity : Dynamic: Not available

Kinematic: Not available

Other information

*Minimum Explosive : 0.015 - 0.100 kg/m3(typical range)

Concentration (MEC)

*Minimum Ignition Energy (MIE) : 3 - 150 mJ (typical range)
*Minimum Ignition Temperature : 490 - 550 °C (typical range)

(MIT)

*Minimum Ignition Temperature : Not available

- Layer

*Kst : 43 - 243 m.b_/s(typical range)
*Pmax : 90 - 128 psi(typical range)

Section 10. Stability and reactivity

Reactivity : Stable under normal conditions.

Chemical stability : The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : Avoid the creation of dust when handling and avoid all possible

^{*} These values listed above are only representative values. A resin's characteristics may change depending upon the process and conditions of use at your facility or any changes made to the resin during use, including further grinding or mixing with other products. In order to obtain more specific data for your particular resin as it is used at your facility, we recommend that you conduct your own characterization testing.

EPONTM Resin 1007F

sources of ignition (spark or flame). Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Prevent dust accumulation. See Section 7 Handling.

Incompatible materials

Reactive or incompatible with the following materials: oxidizing materials acids

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other hazards

Reacts with considerable heat release with some curing agents.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4,4'-Isopropylidenediphenol				
	LD50 Oral	Rat	3,250 mg/kg	-
	LD50 Dermal	Rabbit	3,000 mg/kg	-

Conclusion/Summary : Not available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-Isopropylidenediphenol	Skin - Erythema/E schar 404 Acute Dermal Irritation/Co rrosion	Rabbit	0	4 hrs	1 - 72 hrs
	Skin - Edema 404 Acute Dermal Irritation/Co	Rabbit	0	4 hrs	1 - 72 hrs
	eyes - Cornea opacity 405 Acute Eye Irritation/Co rrosion	Rabbit	1		-
	eyes - Iris lesion 405 Acute Eye Irritation/Co rrosion	Rabbit	1		-

EPONTM Resin 1007F Page: 10/16

eyes -	Rabbit	1	-
Redness of			
the			
conjunctiva			
e 405			
Acute Eye			
Irritation/Co			
rrosion			
eyes -	Rabbit	1 - 2	-
Edema of			
the			
conjunctiva			
e 405			
Acute Eye			
Irritation/Co			
rrosion			

Conclusion/Summary

Skin:Not availableeyes:Not availableRespiratory:Not available

Sensitization

Conclusion/Summary

Skin: Not availableRespiratory: Not available

Mutagenicity

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

Reproductive toxicity

Conclusion/Summary: See below for potential chronic health effects

Teratogenicity

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
4,4'-Isopropylidenediphenol	Category 3		Respiratory tract irritation
	Category 2		central nervous system
	Category 3		(CNS)
	Category 2		Respiratory tract irritation
			central nervous system
			(CNS)

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs	
i i i vuuc <i>u</i> mei cuiciit name	Category	INDUIC OF CADOSUIC	I al ect of earls	

EPONTM Resin 1007F Page: 11/16

4,4'-Isopropylidenediphenol	Category 2	bladder
		kidneys
		liver
		bladder
		kidneys
		liver

Aspiration hazard

Not available

Information on likely routes of

exposure

Not available

Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects: Not availablePotential delayed effects: Not available

Long term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
4,4'-Isopropylidenediphenol		•		=
Remarks:	Bisphenol A (BPA) has been extensively te	sted in a wide variet	y of toxicological
	and biological tests	s, and has undergone mar	ny reviews internation	onally by a variety of
	governmental agencies. Many of these studies have focused on reproductive,			
	developmental and endocrine endpoints. However, the human data is limited and			
	insufficient to evaluate reproductive toxicity. While some studies show, or claim to			
	show, target organ	toxicity, fertility, or repr	oductive effects in h	umans; these studies
	lack internal and external validity as a result of flawed study design, multiple			
	sources of bias, and	d lack of control for conf	ounding factors.	

EPONTM Resin 1007F Page: 12/16

Numerous animal studies have been conducted and report a range of potential reproductive effects from BPA exposure. Although some studies report reproductive effects, many of these studies suffer from design flaws and reported observations have not been confirmed in larger, more robust studies. Comprehensive reviews of the scientific literature on BPA have focused on several well designed animal studies as a robust foundation for assessing BPA reproductive toxicity (e.g., NTP 1985; Ema et al. 2001; Tyl et al. 2002a, 2002b; Tyl et al. 2008; Delclos et al. 2014). In these studies, BPA was administered to rats and/or mice by the oral route of exposure including doses that far exceed those potentially experienced by humans, including workers. In these studies, either no reproductive toxicity was reported, or treatment-related reproductive effects were reported only at doses where maternal toxicity was observed. Maternal toxicity was manifest as liver toxicity, kidney toxicity, and overall depressions in body weight or body weight gains. The presence of these clear toxic effects was consistent with the role of stress and general systemic toxicity in the development of the reproductive effects at these high doses of BPA. The authors of these studies all concluded that systemic toxicity played a role in the observation of the reproductive effects.

By letter dated April 6, 2015, the U.S. Food and Drug Administration ("FDA") of the U.S. Department of Health & Human Services reported that FDA's National Center of Toxicological Research ("NCTR") "recently completed a large scale rodent toxicity study designed to characterize potential effects of BPA in a wide range of endpoints, including reproductive toxicity.... The results from the large extent of reproductive, sperm and hormone parameters evaluated in the NCTR study do not support BPA as a reproductive toxicant."

Based on the total weight of evidence of the experimental animal data, including the lack of robust epidemiological data for reproductive effects, well-established pharmacokinetic data and the results of FDA's recent large scale toxicity study and using expert judgment, there is insufficient scientific support to associate reproductive toxicity with BPA exposure in the absence of systemic toxicity. Because experimental animal studies have indicated potential for reproductive effects in association with maternal toxicity at high doses, BPA has been classified as a Category 2 suspected human reproductive toxicant as required by OSHA.

Conclusion/Summary

Not available

General

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
No known significant effects or critical hazards.
No known significant effects or critical hazards.

Carcinogenicity Mutagenicity Teratogenicity Developmental effects

No known significant effects or critical hazards.
No known significant effects or critical hazards.
No known significant effects or critical hazards.

Fertility effects

: Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Not available

Section 12. Ecological information

Toxicity

EPONTM Resin 1007F Page: 13/16

Product/ingredient name Result		Species	Exposure
bisphenol A			
	Acute LC50 4.6 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute No-observable-effect-concentration 0.016 mg/l Fresh water	Fish - Fathead minnow	444 d
	Chronic ecotoxicity		
	Acute EC50 1 - 16 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute No-observable-effect- concentration 1.8 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 2.73 mg/l Fresh water	Aquatic plants - Microalgae	96 h
	Chronic No-observable-effect- concentration 0.016 mg/l Fresh water	Fish - Fathead minnow	444 d
	Chronic No-observable-effect- concentration 1.8 mg/l Fresh water	Aquatic invertebrates. Water flea	-

Conclusion/Summary : Not available

Persistence/degradability

Conclusion/Summary : Not available

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
4,4'-Isopropylidenediphenol	3.4	73	low

Mobility in soil

Soil/water partition coefficient

(KOC)

Not available

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

EPONTM Resin 1007F Page: 14/16

Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regulations

Regulatory UN/NA Proper shipping name Classes/*PG Reportable information number Quantity (RQ)

CFR Non-regulated

TDG Non-regulated

IMO/IMDG Non-regulated

Non-regulated IATA (Cargo)

*PG: Packing group

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

U.S. Federal regulations

United States - TSCA 12(b) - Chemical export notification: None required.

United States - TSCA 5(a)2 - Final significant new use rules: Not listed United States - TSCA 5(a)2 - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed SARA 311/312 Classification - Immediate (acute) health hazard, Delayed (chronic) health hazard

California Prop. 65:

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer., WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

United States inventory (TSCA: 8b)

All components are listed or exempted.

International regulations

International lists Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

17.1 10/27/2017 05/30/2015 Version: Date of issue/Date of revision: Date of previous issue:

EPONTM Resin 1007F Page: 15/16

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. United States inventory (TSCA 8b): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System III (U.S.A.):

Health	*	1
Flammability		3
Physical hazards		0
	•	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Full text of abbreviated H

statements

Not applicable.

History

Date of printing: 03/13/2018Date of issue/Date of revision: 10/27/2017Date of previous issue: 05/30/2015Version: 17.1

Prepared by
Rey to abbreviations
Product Safety Stewardship
ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

UN = United Nations

References : Not available

Notice to reader

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. HEXION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR

EPONTM Resin 1007F Page:16/16

ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.

® and ™ Licensed trademarks of Hexion Inc.

Date of previous issue: 05/30/2015 Version: 17.1 10/27/2017 Date of issue/Date of revision: