



1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: MS-552N
DPMS-N0616B-2
Cleaning Solvent & Flux Remover

Product Use: Solvent Cleaning & Flux Removal
for electronic assemblies

MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical
55 Backus Ave
Danbury, Conn. 06810 USA
(203) 743-4447

Emergency Phone Number:
(800) 424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

Serious Eye Damage/Irritation: Category 2B.
Specific Target Organ Toxicity (single exposure): Category 3.

Label elements:

Signal word

Warning

Pictogram



Hazard Statements

Causes eye irritation.
May cause drowsiness or dizziness.

Prevention Statements

Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/ container to an approved waste disposal plant.

Other Hazards

In use, may form flammable/explosive vapor-air mixture. Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may lead to death without warning symptoms, due to cardiac effects. Rapid evaporation of the product may cause frostbite.

3. INGREDIENTS

| <u>Material (s)</u> | <u>CAS No.</u> | <u>Approximate %</u> |
|---------------------------------------|----------------|----------------------|
| 1,1,1,2,2,3,4,5,5,5-Decafluoropentane | 138495-42-8 | 25 – 35 |
| Trans,1,2-Dichloroethylene | 156-60-5 | 65 – 75 |

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Eye: Immediately, flush with large amounts of water for at least 15 minutes, lifting eyelids until no evidence of the chemical remains. Remove contact lenses, if present and easy to do. Continue to rinse. Get medical attention.

Skin: Wash skin with plenty water after contact. Remove contaminated clothing and shoes. Wash contaminated clothing and clean shoes before use. Get medical attention.

Oral: DO NOT induce vomiting without medical advice. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed: May cause cardiac arrhythmia.

Skin contact may provoke the following symptoms: Dermatitis, Discomfort, Pain, Superficial burning sensation, Redness, Rash, Itching, Swelling of tissue, Irritation

Eye contact may provoke the following symptoms: Irritation, Tearing, Discomfort, Redness

Effects of breathing high concentrations of vapor may include: Tiredness, Drowsiness, confusion, Dizziness, central nervous system effects, Convulsions.

Adverse effects from repeated inhalation may include central nervous system effects

Aspiration may cause pulmonary edema and pneumonitis. Causes eye irritation. May cause drowsiness or dizziness.

Notes to Physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Flash Point: Does not flash.

Test Method: Pensky-Martens closed cup

Suitable Extinguishing Media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO₂)

Unsuitable extinguishing media: None known.

Special hazards: Vapors may form explosive mixture with air. Exposure to combustion products may be a hazard to health.

Hazardous combustion products: Hydrogen fluoride, Fluorine compounds, Carbonyl fluoride, Carbon oxides, Chlorine compounds.

Specific extinguishing methods: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers with water spray.

Special protective equipment for fire-fighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel): Evacuate personnel to safe area. Ventilate area, especially low or enclosed places where heavy vapors might collect. In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental precautions: If containers rupture, prevent material from entering sewers, waterways, or low areas. Should not be released into the environment. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Spill Cleanup: Contain spillage, and then collect with inert absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations

7. HANDLING AND STORAGE

Handling: Use in a well-ventilated area to avoid breathing vapors. Use with exhaust ventilation. Use appropriate respiratory protection when ventilation is inadequate. Use only in an area equipped with explosion-proof exhaust ventilation. Keep away heat and sources of ignition. Take precautionary measures against static discharges. When using do not eat, drink, or smoke. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Storage Conditions: Store tightly sealed in a clean, dry place, and well-ventilated place. Keep in properly labeled containers. Do not store in temperatures that exceed 125°F/52°C, because the containers could leak or rupture from pressure and expansion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

| <u>Exposure Limits:</u> | <u>TLV (ACGIH)</u> | <u>PEL (OSHA)</u> |
|---------------------------------------|--------------------|--------------------|
| 1,1,1,2,2,3,4,5,5,5-Decafluoropentane | Not Established | Not Established |
| Trans,1,2-Dichloroethylene | 200 ppm, TWA | 200 ppm, 8 Hr. TWA |

Respiratory Protection: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Use gloves impervious to this material (eg. Viton) when prolonged or frequently repeated contact occurs. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 122°F/50°C

Percent Volatile by Volume: 100

Density: 1.35 g/cc @ 77°F/25°C

Vapor Pressure: 349 mmHg @ 77°F/25°C

Vapor Density (Air=1): N.A.

Solubility in H₂O: N.A.

pH Information: Neutral

Evaporation Rate (CC14=1): N.A.

Form: Liquid

Appearance: Clear & Colorless

Color: Colorless

Odor: Slight

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Vapors may form flammable mixture in the air. In use may form flammable/explosive vapor-air mixture.

Material and Conditions to Avoid: None known.

Hazardous decomposition products: No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Trans-1,2-Dichloroethylene

Acute Oral: LD50: 7902 mg/kg in rats

Acute Dermal: LD50: > 5,000 mg/kg in rabbits

Acute Inhalation: 4 hour LC50: 95.4 mg/l in rats. Test atmosphere: vapor. Method: OECD Test Guideline 403

Skin Corrosion/Irritation: Mild skin irritation in rabbits

Serious Eye Irritation/ Eye Irritation: Mild eye irritation in rabbits. Reversing within 7 days.

Skin Sensitization: Not classified based on available information.

Respiratory Sensitization: Not classified based on available information.

Germ Cell Mutagenicity: Evidence does not support classification of a germ cell mutagen.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Not classified based on available information.

STOT-single exposure: May cause drowsiness and dizziness.

STOT-repeated exposure: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Aspiration toxicity: Not classified based on available information.

12. ECOLOGICAL INFORMATION

Trans-1,2-Dichloroethylene

96 hour LC50 in Lepomis marochirus (Bluegill sunfish): 135 mg/l

48 hour EC50 in Daphnia magna (Water flea): 220 mg/l

72 hour EC50 in Pseudokirchneriella subcapitata (Green algae): 36.36 mg/l

Biodegradability: Not readily biodegradable. Method: OECD Test Guideline 301D

Bioaccumulative potential: Partition coefficient: n-octanol/water: log Pow: 2.06

13. DISPOSAL CONSIDERATIONS

If recycling is not practicable, dispose of in compliance with local regulations. Remove to a permitted waste disposal facility. The product should not be allowed to enter drains, water courses or the soil.

14. TRANSPORT INFORMATION

U.S. DOT

Not Regulated

IATA

Not Regulated

IMDG

Not Regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA: All ingredients are listed in TSCA inventory.

1,1,1,2,2,3,4,5,5,5-DECAFLUOROPENTANE (CAS# 138495-42-8) is controlled by TSCA Section 5, Significant New Use Rule (SNUR; 40 CFR 721.5645) The approved uses are: precision and general cleaning, carrier fluid, displacement drying, printed circuit board cleaning, particulate removal, film cleaning, process medium, heat transfer fluid (dielectric and non-dielectric), and test fluid. Processors and users of this substance must also comply with the applicable general SNUR requirements set forth in 40 CFR 721 subpart A, including export notification requirements if applicable (40 CFR 721.20), and the applicable record keeping requirements set forth at 40 CFR 721.125.

SARA 304 Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity: This material does not contain any components with a section 302 EHS RQ.

SARA 311/312 Hazards: Serious eye damage or eye irritation. Specific target organ toxicity (single or repeated exposure).

SARA 313 Regulated Chemicals: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Proposition 65: This product does not contain any chemicals known to the State of California to cause cancer and/or birth defects or other reproductive defects.

16. OTHER INFORMATION

NPCA-HMIS Ratings:

Health - 1

Flammability - 0

Reactivity - 0

Personal Protective rating to be supplied by user depending on the conditions.

FOR INDUSTRIAL USE ONLY

REVISION DATE: SEPTEMBER 2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.