



Contact Re-Nu[®]

MS-530 (Aerosol)

MS-532 (Bulk Liquid)

A cleaning agent that restores electrical or mechanical continuity on all types of contacts. Excellent for cleaning oxides, oil, grease and dust from contacts, switches, relays, tuners, encoders, slide wires, rheostats, distribution panels and servomechanisms. Evaporates quickly and leaves no residue.

ADVANTAGES:

- Evaporates quickly
- Leaves no residue
- RoHS compliant

TYPICAL PROPERTIES:

Boiling Point..... 98°F /37°C
 Liquid Density.....1.33 g/ml @ 77°F/25°C
 Ozone Depletion.....0.00
 VOC Content of MS-530.....437g/l
 VOC Content of MS-532.....375g/l

PLASTIC COMPATIBILITY:

(Immersion: 15 minutes at Room Temperature)

- | | |
|-----------------------|------------------------|
| • Acetal | Polyethylene |
| • Polypropylene | Liquid Crystal Polymer |
| • Polyester, PBT, PET | Epoxy |
| • Polysulfone, PSO | PEK, PEEK |
| • Polyimides | PTFE |
| • Phenolic | Polyvinylchloride |

NOTE: Acrylics, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use.

ELASTOMER COMPATIBILITY:

(Immersion: 15 mins at Room Temperature)

- | | |
|------------------------|----------------|
| • Butyl Rubber | Natural Rubber |
| • Polysulfide | EPDM |
| • Buna S | Buna N |
| • Neoprene | Urethane |
| • Chlorosulfonated PE | Silicone |
| • Viton [™] B | |

Elastomer swelling and shrinking will, in most cases, revert to within a few percent of original size after air drying. Swell, shrinkage, and extractables are strongly affected by the compounding agents, plasticizers, and curing used in the manufacture of the elastomers. Test for compatibility before use.

METAL COMPATIBILITY:

(Immersion: 2 weeks at 99°F/37°C)

- Aluminum
- Copper
- Iron

Note: Test for compatibility before use.

Safety Data Sheets (SDS) are available upon request.

For technical support:

800-992-2424 (8-4 E T) in the U.S.

800-323-4621 (8-4 E T) in Canada.

e-mail: support@mschem.com

www.miller-stephenson.com

Viton[™] is a trademark of The Chemours Co. FC, LLC.

Contact Re-Nu[®] is a registered trademark of miller-stephenson chemical company inc.

1448-6K

The recommendations made here with and the information set forth with respect to the performance or use of our products are believed, but not warranted to be accurate. The products discussed are sold without warranty, as to fitness or performance, express or implied and upon condition that purchasers shall make their own test to determine suitability of such products for their particular purposes. Likewise, statements concerning the possible uses of our products are not intended as recommendations to use our products in the infringement of any patent.

CONNECTICUT
 Miller-Stephenson Chemical Co., Inc.
 55 Backus Avenue
 Danbury, Connecticut 06810 U.S.A.
 203 743-4447 Fax 203 791-8702

ILLINOIS
 Miller-Stephenson Chemical Co., Inc.
 6348 Oakton Street
 Morton Grove, Illinois 60053 U.S.A.
 847 966-2022 Fax 847 966-8468

CALIFORNIA
 Miller-Stephenson Chemical Co., Inc.
 12261 Foothill Boulevard
 Sylmar, California 91342 U. S. A.
 818 896-4714 Fax 818 896-6086

CANADA
 Miller-Stephenson Chemical Co., Inc.
 280 Belfield Road
 Toronto, Ontario M9W 1H6 Canada
 416 675-3204 Fax 416 674-2987