



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : Vertrel™ SFR specialty fluid, Vertrel™ SFR specialty fluid

Product code : D14830229, D14830229

SDS-Identcode : 130000033961

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19899 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent

Restrictions on use : For professional and industrial installation and use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Eye irritation : Category 2B

Specific target organ systemic toxicity - single

exposure

Category 3

GHS label elements

Hazard pictograms

Signal Word : Warning

Hazard Statements : H320 Causes eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors. P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON

CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ atten-

tion.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

In use, may form flammable/explosive vapor-air mixture.

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
trans-Dichloroethylene	156-60-5	>= 50 - < 70
Methanol	67-56-1	>= 1 - < 3

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.





Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

May cause cardiac arrhythmia.

Skin contact may provoke the following symptoms:

Dermatitis Irritation

Pain

superficial burning sensation

Itching Redness

Swelling of tissue

Rash Discomfort

Eye contact may provoke the following symptoms

Irritation tearing Discomfort Redness

Effects of breathing high concentrations of vapor may include:

Tiredness Drowsiness

central nervous system effects

Convulsions Dizziness confusion

Adverse effects from repeated inhalation may include

central nervous system effects

Aspiration may cause pulmonary edema and pneumonitis.

Causes eye irritation.

May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection.

and use the recommended personal protective equipment

when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

: Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Hazardous combustion prod: :

ucts

Carbon oxides
Chlorine compounds
Hydrogen fluoride
carbonyl fluoride
Fluorine compounds

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure

potential





Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Advice on safe handling : Do not get on skin or clothing.

Do not breathe vapors or spray mist.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage

Do not expose drums to direct heat or temperature above 46°C (115°F) to avoid pressurizing and possibly distorting the

drums.

Material should not be dispensed by pouring from pail/drum shipping containers containing 5 gallons or more. The use of a drum pump is recommended for dispensing from pail/drum shipping containers with 5 gallons or more, except for smaller containers where adequate ventilation can be used to manage

the exposure.

Keep in properly labeled containers.

Store locked up.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Recommended storage tem-

perature

< 46 °C

Storage period : > 10 y

Further information on stor-

age stability

: The product has an indefinite shelf life when stored properly.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
trans-Dichloroethylene	156-60-5	TWA	200 ppm	ACGIH
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m ³	NIOSH REL
		ST	250 ppm 325 mg/m ³	NIOSH REL
		TWA	200 ppm 260 mg/m ³	OSHA Z-1

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures : Minimize workplace exposure concentrations.

Use only in an area equipped with explosion-proof exhaust ventilation if advised by assessment of the local exposure

potential

Use with local exhaust ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Viton (R)
Glove thickness : 0.7 mm
Wearing time : 120 min

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the

product. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.





Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Wear the following personal protective equipment: Flame retardant antistatic protective clothing, unless assessment demonstrates that the risk of explosive

atmospheres or flash fires is low

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless, clear

Odor : slight, pleasant

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : < -50 °C

Initial boiling point and boiling

range

41 °C

Flash point : Method: Pensky-Martens closed cup

does not flash

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

Upper flammability limit

15 %(V)

Method: ASTM E681

Lower explosion limit / Lower

flammability limit

Lower flammability limit

7 %(V)

Method: ASTM E681

Vapor pressure : 579 hPa (25 °C)

Relative vapor density : 2.4

Density : 1.28 g/cm³ (25 °C)

Solubility(ies)

Water solubility : No data available





Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : In use may form flammable/explosive vapor-air mixture.

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Vapors may form explosive mixture with air.

Can react with strong oxidizing agents.

In use may form flammable/explosive vapor-air mixture.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 101.85 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method





 Version
 Revision Date:
 SDS Number:
 Date of last issue: 09/05/2017

 7.0
 10/17/2017
 1333549-00034
 Date of first issue: 02/27/2017

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Ingredients:

trans-Dichloroethylene:

Acute oral toxicity : LD50 (Rat): 7,902 mg/kg

Acute inhalation toxicity : LC50 (Rat): 95.4 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Lowest observed adverse effect concentration (Dog): 250000

ppm

Cardiac sensitisation threshold limit (Dog): 991,309 mg/m³

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

trans-Dichloroethylene:

Species: Rabbit

Result: Mild skin irritation

Methanol:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Causes eye irritation.

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Ingredients:

trans-Dichloroethylene:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Methanol:

Species: Rabbit

Result: No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Ingredients:

Methanol:

Test Type: Maximization Test Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

trans-Dichloroethylene:

Germ cell mutagenicity -

Assessment

: Weight of evidence does not support classification as a germ

cell mutagen.

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Carcinogenicity

Not classified based on available information.





Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Ingredients:

Methanol:

Species: Mouse

Application Route: inhalation (vapor)

Exposure time: 18 Months

Result: negative

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:

Methanol:

Effects on fertility : Test Type: Fertility/early embryonic development

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

Result: positive

Remarks: The effects were seen only at maternally toxic dos-

es.

STOT-single exposure

May cause drowsiness or dizziness.

Ingredients:

trans-Dichloroethylene:

Assessment: May cause drowsiness or dizziness.

Methanol:

Target Organs: Eyes, Central nervous system Assessment: Causes damage to organs.

STOT-repeated exposure

Not classified based on available information.

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Ingredients:

trans-Dichloroethylene:

Assessment: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity

Ingredients:

trans-Dichloroethylene:

Species: Rat NOAEL: 4000 ppm LOAEL: > 4000 ppm

Application Route: inhalation (gas)

Exposure time: 90 d

Method: OECD Test Guideline 413

Remarks: No significant adverse effects were reported

Species: Rat

NOAEL: 3,000 mg/kg LOAEL: > 3,000 mg/kg Application Route: Ingestion

Exposure time: 90 d

Remarks: No significant adverse effects were reported

Methanol:

Species: Rat NOAEL: 1.06 mg/l

Application Route: inhalation (vapor)

Exposure time: 90 Days

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

trans-Dichloroethylene:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 135 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 220 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 36.36

mg/l

Exposure time: 72 h

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000

mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l

Exposure time: 200 h

Toxicity to microorganisms : IC50: > 1,000 mg/l

Exposure time: 3 h

Persistence and degradability

Ingredients:

trans-Dichloroethylene:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

Methanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 95 % Exposure time: 20 d

Bioaccumulative potential

Ingredients:

trans-Dichloroethylene:

Partition coefficient: n-

octanol/water

log Pow: 2.06

Methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): < 10

Partition coefficient: n-

octanol/water

log Pow: -0.77

Mobility in soil

No data available

Other adverse effects

No data available

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(trans-Dichloroethylene)

Class : 9 Packing group : III

Labels : CLASS 9
ERG Code : 171
Marine pollutant : no

Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE

SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS

THE REPORTABLE QUANTITY.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
trans-Dichloroethylene	156-60-5	1000	1466
Methanol	67-56-1	5000	169744

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.





Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Methanol 67-56-1 >= 1 - < 5 %

US State Regulations

Pennsylvania Right To Know

trans-Dichloroethylene 156-60-5 1,1,1,2,2,3,4,5,5,5-Decafluoropentane 138495-42-8 1,1,2,2,3,3,4-Heptafluorocyclopentane 15290-77-4 Methanol 67-56-1

California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

trans-Dichloroethylene 156-60-5 Methanol 67-56-1

California Permissible Exposure Limits for Chemical Contaminants

Methanol 67-56-1

Additional regulatory information

1,1,1,2,2,3,4,5,5,5- 138495-42-8

Decafluoropentane

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

1,1,2,2,3,3,4- 15290-77-4

Heptafluorocyclopentane

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.

See 40 CFR § 721.10434

Vertrel™ SFR specialty fluid




Version **Revision Date:** SDS Number: Date of last issue: 09/05/2017 1333549-00034 Date of first issue: 02/27/2017 7.0 10/17/2017

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Vertrel™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

Full text of other abbreviations

ACGIH USA. ACGIH Threshold Limit Values (TLV) ACGIH BEI ACGIH - Biological Exposure Indices (BEI) NIOSH REL USA. NIOSH Recommended Exposure Limits

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA 8-hour, time-weighted average ACGIH / STEL Short-term exposure limit

NIOSH REL / TWA Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals

Vertrel™ SFR specialty fluid



Version Revision Date: SDS Number: Date of last issue: 09/05/2017 7.0 10/17/2017 1333549-00034 Date of first issue: 02/27/2017

in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan): ISO - International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG -United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 10/17/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8