



1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: ShieldSys SB Product Use: Dry Film Medical Coatings

P0120B

Dry Film Water Dispersion

MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical 55 Backus Ave. Danbury, Conn. 06810 USA (203) 743-4447 Emergency Phone Number: (800) 424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

Serious eye damage/eye irritation: Category 2A

Label elements: Signal word

Warning

Pictograms



Hazard Statements

Causes serious eye irritation.

Precautionary Statements

Wash skin thoroughly after handling.

Wear protective gloves/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Other Hazards

The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Repeated episodes of polymer fume fever may result in persistent lung effects.

3. INGREDIENTS

Material (s) CAS No. Approximate %

Polyethylene oxide mono-C9-11-alkyl ether 68439-46-3 1 – 5%

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air. If not breathing, give artificial respiration. Give oxygen as necessary, if qualified personnel is available. Get medical attention if necessary.

Eye: Flush with large amounts of water. Remove contact lenses, if present and easy to do. If eye irritation persists, consult a specialist.

Skin: Wash well with water. Remove contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if necessary.

Oral: DO NOT induce vomiting unless directed to do so by a physician. Never give anything to an unconscious person. Call a physician.

5. FIRE FIGHTING MEASURES

Flash Point: Does not flash. **Thermal decomposition:** 300°C (572°F)

Extinguishing Media: This product does not burn. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific Hazards: Toxic decomposition products may be formed. (See section 10)

Special Fire Fighting Instruction: Evacuate personnel to safe areas. Wear suitable protective equipment. Wear self-contained breathing apparatus (SCBA), if necessary under fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Evacuate personnel, ventilate area with fresh air, if a large amount is accidental released, use self-contained breathing apparatus. Dike spill. Prevent material from entering sewers, waterways or low areas. Soak up with inert absorbent materials (e.g. sand, silica gel, acid binder, universal binder, sawdust).

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes or clothing. Avoid breathing vapors or spray mist. Wash thoroughly after handling. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material.

Storage Conditions: Keep containers tightly closed in a dry, cool, and well-ventilated place. Do Not Freeze. Product is perishable frozen. Store at $50 - 81^{\circ}F$ ($10 - 27^{\circ}C$).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection: Provide adequate ventilation. Wear suitable respiratory protection, when ventilation is insufficient.

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Where there is potential for skin contact, have available and wear as appropriate,

impervious gloves, apron, pants and jacket.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 212°F/100°C **Percent Volatile by Volume:** 78 - 82%

Density: 1.13 g/cc **Vapor Pressure:** 24 mm Hg at 77°F/25°C

Vapor Density (Air=1): >1 **Solubility in H₂O:** Dispersible

pH Information: 9 - 10 Evaporation Rate (CC14=1): N. A.

Form: Liquid Appearance: Milky

Color: White Odor: Faint Sweet Odor

10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions.

Material and Conditions to Avoid: Decomposition temperature 300°C /572°F. Incompatible with alkali metals, alkaline earth

metals, strong oxidizers, molecular sieves.

Decomposition: This product decomposes with heat (300°C/572°F) forming fluorinated compounds and carbon oxides.

Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: None of the components in this product are listed as a carcinogen by IARC, NTP, OSHA, or ACGIH.

Polyethylene oxide mono-C9-11-alkyl ether

Dermal LD50: 2,000 - 5,000 mg/kg, Rabbit

Oral LD50: 1,100 mg/kg, Rat

Skin irritation: Severe skin irritation, Rabbit **Eye irritation:** Severe eye irritation, Rabbit

Repeated dose toxicity: Dermal, Rat: Skin effects. Thickening of skin. Oral, Rat: No toxicologically significant effects were found.

Reproductive toxicity: Evidence suggests the substance is not a reproductive toxin in animals.

Teratogenicity: Evidence suggests the substance is not a developmental toxin in animals.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity:

Polyethylene oxide mono-C9-11-alkyl ether

96 hour LC50 Pimephales promelas (fathead minnow): 8.5 - 11.0 mg/l 48 hour EC50 Daphnia magna (Water flea) 2.7 - 12 mg/l

Environmental Fate:

Polyethylene oxide mono-C9-11-alkyl ether

Bioaccumulation: 80% - Readily biodegradable. **Bioaccumulation:** Bioaccumulation is unlikely.

Other adverse effects: No data is available on the product itself.

13. <u>DISPOSAL CONSIDERATIONS</u>

Waste Disposal: In accordance with local and national regulations.

Environmental Hazards: If recycling is not practicable, dispose of in compliance with local regulations.

14. TRANSPORT INFORMATION

U.S. DOT

Not Regulated

IATA

Not Regulated

IMDG

Not Regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA: All ingredients are listed in TSCA inventory.

SARA/TITLE III HAZARD CATEGORIES:

Product Hazard Categories:

Acute Health - Yes
Chronic Health - Yes
Fire Hazard - No
Reactivity Hazard - No
Pressure Hazard - No

16. OTHER INFORMATION

NPCA-HMIS Ratings:

Health - 1 Flammability - 0 Reactivity - 0

Personal Protective rating to be supplied by user depending on the conditions.

FOR INDUSTRIAL USE ONLY

DATE: JUNE 2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.