



## 1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: MS-122AV Product Use: Release Agent or Dry Lubricant

DPMS-N0426A-1 PTFE Release Agent/Dry Lubricant

## MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical 55 Backus Ave. Danbury, Conn. 06810 USA (203) 743-4447 Emergency Phone Number: (800) 424-9300

## 2. HAZARDS IDENTIFICATION

Physical Hazard: Gases under pressure – Liquefied Gas

## Label elements:



**Single Word:** Warning **Hazard Statements** 

Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation.

## **Precautionary Statements:**

Avoid breathing mist/vapor/spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Remove/Take off all contaminated clothing, immediately. Rinse skin with water.

IF INHALED: Remove victim to fresh air and keep at rest in position comfortable for breathing.

Protect from sunlight. Do not expose to temperature exceeding  $50^{\circ}\text{C}/122^{\circ}\text{F}$ .

Do not spray on an open flame or other ignition source.

Pressurized container. Do not pierce or burn, even after use.

Dispose of contents/container to an approved waste disposal plant.

## Other hazards which do not result in classification or are not covered by GHS

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing.

The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

## 3. INGREDIENTS

<u>Material (s)</u>	CAS No.	<u>Approximate %</u>
1,1,1,2-Tetrafluoroethane	811-97-2	90 - 95
Isopropyl Alcohol	67-63-0	5 - 10

### 4. FIRST AID MEASURES

**Inhalation:** Remove patient to fresh air. Get medical attention.

**Eye:** Immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Continue to rinse. Get medical attention.

**Skin:** Immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before use. Thoroughly clean shoes before reuse. Get medical attention.

**Oral:** DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed: Inhalation of decomposition products may provoke the following symptoms: Polymer fume fever. Eye contact may provoke the following symptoms: Irritation Causes serious eye irritation. May cause drowsiness or dizziness. Other symptoms potentially related to misuse or inhalation abuse are: Cardiac sensitization, Anaesthetic effects, Light-headedness, confusion, Lack of coordination, Unconsciousness

## 5. FIRE FIGHTING MEASURES

**Specific hazards:** This product is not flammable.

Fire and Explosion: Aerosols may rupture under fire conditions. Decomposition may occur.

**Extinguishing Media:** As appropriate for surrounding area.

**Special Fire Fighting Instruction:** Self-contained breathing apparatus (SCBA) maybe required if a large amount of aerosols rupture under fire conditions. Evacuate personnel to safe area. Fight fire from a distance, heat may rupture containers.

## 6. ACCIDENTAL RELEASE MEASURES

Ventilate area with fresh air, if a large amount is accidental released and wear self-contained breathing apparatus. No need for additional release information, since it is an aerosol.

## 7. HANDLING AND STORAGE

**Handling:** Use in a well-ventilated area to avoid breathing vapors. Vapors are heavier than air and accumulate in low areas. Use only with adequate ventilation. Where ventilation is inadequate, use appropriate respiratory protection. Avoid contact with skin or eyes. Wash thoroughly after handling. Polytetrafluoroethylene should not be handled around tobacco products because, smoking contaminated tobacco products may cause polymer fume fever.

Storage Conditions: Do not store near sources of heat, in direct sunlight or where temperatures exceed 120°F/49°C

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:TLV (ACGIH)PEL (OSHA)1,1,1,2-TetrafluoroethaneNot EstablishedNot EstablishedIsopropyl Alcohol200 ppm , TWA400 ppm , 8 Hr. TWA

Respiratory Protection: Avoid breathing vapors, mists or spray. Use with mechanical ventilation especially for enclosed or low

places. Local exhaust should be used when large amounts are released. If necessary to keep exposure limits below permissible limits, use NIOSH approved respirators. In poorly ventilated areas, use an approved self-

contained breathing apparatus.

**Eve Protection:** Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Use gloves impervious to this material when prolonged or frequently repeated

contact occurs.

**Prevention of Swallowing:** Do not eat, drink or smoke when using this product. Wash hands thoroughly after contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Boiling Point:** Not Applicable **Percent Volatile by Volume:** 99%

**Density:** 1.2 g/cc at 77°F/25°C **Vapor Pressure:** 80 psig at 77°F/25°C

**Vapor Density (Air=1):** >1 **Solubility in H<sub>2</sub>O:** Insoluble

**pH Information:** Neutral **Evaporation Rate (CC14=1):** >1

Form: Aerosol Appearance: Milky

**Color:** White **Odor:** Faint Ethereal Odor

## 10. STABILITY AND REACTIVITY

**Stability:** Stable at normal and storage conditions.

Material and Conditions to Avoid: Avoid heat, sparks and flame. Strong oxidizers.

**Decomposition:** This product can be decomposed by high temperatures (flame, glowing metal surfaces, etc.) forming Hydrofluroric acid, Carbonyl difluoride, hazardous gases including Carbon monoxide and Carbon dioxide.

Polymerization: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### 1,1,1,2-Tetrafluoroethane

## **Acute Inhalation:**

4 hour, LC50 rat: >567000 ppm

Cardiac sensitization Species: Dogs

Note: Lowest observed adverse effect concentration: 80000 ppm. Cardiac sensitisation threshold limit: 334,000 mg/m3.

Skin corrosion/irritation: No skin irritation in rabbits.

Serious eye damage/eye irritation: No eye irritation in rabbits.

**Respiratory or skin sensitization:** Not classified based on available information.

Germ cell mutagenicity: Not classified based on available information.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Not classified based on available information.

STOT-single exposure: Not classified based on available information.

STOT-Repeated exposure: Not classified based on available information.

### Isopropyl Alcohol

Acute Oral Toxicity: LD50, Rat: > 5,000mg/kg

Acute Inhalation Toxicity: 6 hour, LC50, Rat: > 25mg/l (vapor)

**Acute Dermal Toxicity:** LD50, Rabbit: > 5,000 mg/kg **Skin Corrosion/Irritation:** No skin irritation in rabbits

**Serious Eye Irritation/ Eye Irritation:** Eye irritation, in rabbits. Reversing in 21 days.

**Skin Sensitization:** Not classified based on available information

**Respiratory Sensitization:** Not classified based on available information **Germ Cell Mutagenicity:** Not classified based on available information

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Not classified based on available information

STOT-single exposure: May cause drowsiness and dizziness.

**STOT-repeated exposure:** Not classified based on available information **Aspiration toxicity:** Not classified based on available information

### 12. ECOLOGICAL INFORMATION

### Isopropyl Alcohol

**Ecotoxicity:** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Toxic to fish: 96 hour, LC50 in Fathead minnow (Pimephales promelas): 9640 mg/l

Toxic to daphnia and other aquatic invertebrates: 24 hour, EC50 Water flea (Daphnia magna): >10,000 mg/l

**Toxic to microorganisms:** 16 hour, EC50 (Pseudomanas putida): >1,050 mg/l

Persistence and degradability: Rapidly degradable

Bioaccumulative potential: Partition coefficient n-octanol/ water (log Pow): 0.05

Mobility in soil: No data available.

## 1,1,1,2-Tetrafluoroethane

**Toxicity to fish:** 96 hour LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l **Toxicity to daphnia and other:** 48 hour EC50 (Daphnia magna (Water flea)): 980 mg/l

Toxicity to algae: 96 hour ErC50 (algae): 142 mg/l

72 hour NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2 mg/l

Biodegradability: Not readily biodegradable.

Bioaccumulative potential: Partition coefficient n-octanol/ water (log Pow): 1.06

Mobility in soil: No data available

## 13. **DISPOSAL CONSIDERATIONS**

Comply with federal, state and local regulations. Remove to a permitted waste disposal facility. Do not puncture or incinerate cans. Empty aerosol cans before disposal.

### 14. TRANSPORT INFORMATION

#### U.S. DOT

**Proper Shipping Name:** Consumer Commodity

Hazard Class: ORM-D Identification No. None Packing Group: None

#### <u>IATA</u>

**Proper Shipping Name:** Aerosols, Non-Flammable

**Hazard Class: 2.2** 

**Identification No.** UN1950 **Packing Group:** None

#### **IMDG**

Proper Shipping Name: Aerosols, Non-Flammable

Hazard Class: 2.2

**Identification No.** UN1950 Packing Group: None

#### 15. REGULATORY INFORMATION

## **U.S. Federal Regulations**

**TSCA:** All ingredients are listed in TSCA inventory.

## **U.S. State Regulations:**

### California Prop. 65

WARNING: This product can expose you to chemicals including 2,2'-Iminodiethanol, which is/are known to the State of California to cause cancer, and pentadecafluorooctanoic acid, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

# 16. OTHER INFORMATION

# **NPCA-HMIS Ratings:**

Health - 1 Flammability - 0 Reactivity - 0

Personal Protective rating to be supplied by user depending on the conditions.

## FOR INDUSTRIAL USE ONLY

**REVISION DATE: AUGUST 2019** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.