



1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: MS-143ZR
MS-143ZR-2
PTFE Release Agent/Dry Lubricant

Product Use: Release Agent or Dry Lubricant

MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical
55 Backus Ave.
Danbury, Conn. 06810 USA
(203) 743-4447

Emergency Phone Number:
(800) 424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

Serious Eye Damage/Eye Irritation: Category 2A
Specific Target Organ Toxicity (single exposure): Category 3

Label elements:

Signal word

Warning

Pictograms



Hazard Statements

Causes serious eye irritation.
May cause drowsiness or dizziness

Precautionary Statements

Avoid breathing mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wash skin thoroughly after handling.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/ container to an approved waste disposal plant.

Other Hazards

The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Prolong skin contact may cause dermatitis or frostbite. Misuse or intentional inhalation abuse may lead to death without warning symptoms, due to cardiac effects.

3. INGREDIENTS

<u>Material (s)</u>	<u>CAS No.</u>	<u>Approximate %</u>
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	138495-42-8	30 – 36
Trans,1,2-Dichloroethylene	156-60-5	26 – 34
Isopropyl Alcohol	67-63-0	30 – 36

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air. If not breathing, give artificial respiration. Give oxygen as necessary, if a qualified person is available. Get medical attention if necessary.

Eye: Flush with a large amount of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue to rinse. Get medical attention if necessary.

Skin: Wash with water for at least 15 minutes. Remove contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if necessary.

Oral: If swallowed, DO NOT induce vomiting unless directed to do so by a physician. Rinse mouth thoroughly with water. Never give anything to an unconscious person. Get medical attention.

Most important symptoms/effects, acute and delayed: The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco. Eye contact may provoke the following symptoms: Irritation Causes serious eye irritation. May cause drowsiness or dizziness.

5. FIRE FIGHTING MEASURES

Flash point: None (Pensky-Martens closed cup)

Suitable Extinguishing Media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO₂)

Unsuitable extinguishing media: No applicable data available.

Special hazards: Exposure to combustion products may be hazardous to health. Hazardous combustion products: Hydrogen fluoride, Carbonyl fluoride, Carbon oxides, Chlorine compounds.

Special Fire Fighting Instruction: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment

Further information: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

Evacuate personnel, ventilate area with fresh air, if a large amount is accidental released, use self-contained breathing apparatus. Dike spill. Prevent material from entering sewers, waterways or low areas. Soak up with sand, earth, vermiculite or other non-combustible absorbent materials.

7. HANDLING AND STORAGE

Handling: Could form explosive/flammable liquid in air. Use in a well-ventilated area to avoid breathing vapors. Vapors are heavier than air and accumulate in low areas. Use only with adequate ventilation. Use appropriate respiratory protection, when ventilation is inadequate. Avoid contact with skin or eyes. Wash thoroughly after handling. When using do not eat, drink, or smoke.

Storage Conditions: Store in a well-ventilated place and keep container tightly closed. Keep away from heat, sparks and flames. Do not allow stored product to exceed 52°C (125°F) to prevent leakage or potential rupture of container from pressure and expansion.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane
Trans,1,2-Dichloroethylene
Isopropyl Alcohol

TLV (ACGIH)

Not Established
200 ppm, 8 Hr. TWA
400 ppm, TWA

PEL (OSHA)

Not Established
200 ppm, 8 Hr. TWA
400 ppm, 8 Hr. TWA

Respiratory Protection: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Use gloves impervious to this material when prolonged or frequently repeated contact occurs. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often.

Prevention of Swallowing: Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 125°F / 52°C

Percent Volatile by Volume: 97-98%

Density: 1.20 g/cc at 77°F/25°C

Vapor Pressure: 220 mm Hg at 77°F/25°C F

Vapor Density (Air=1): N.A.

Solubility in H₂O : N.A.

pH Information: Neutral

Evaporation Rate (CC14=1): N.A.

Form: Liquid

Appearance: Suspended white solids

Color: Opaque

Odor: Slight

10. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and storage conditions.

Material and Conditions to Avoid: Oxidizing agent. Heat, flames, sparks. Extreme temperatures and direct sunlight.

Decomposition: Carbon oxides, Hydrofluoric acid, Carbonyl difluoride

Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: None of the components in this product are listed as a carcinogen by IARC, NTP, OSHA, or ACGIH.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane

Information on likely routes of exposure: Inhalation, Skin contact, Ingestion, Eye contact

Acute Toxicity: Not classified based on available information.

Skin Corrosion/Irritation: Not classified based on available information.

Serious Eye Irritation/ Eye Irritation: Not classified based on available information.

Skin Sensitization: Not classified based on available information.

Respiratory Sensitization: Not classified based on available information

Germ Cell Mutagenicity: Not classified based on available information.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Not classified based on available information.

STOT-single exposure: Not classified based on available information.

STOT-repeated exposure: Not classified based on available information.

Aspiration toxicity: Not classified based on available information.

Trans-1,2-Dichloroethylene

Acute Oral: LD50: 7902 mg/kg in rats

Acute Dermal: LD50: > 5,000 mg/kg in rabbits

Acute Inhalation: 4 hour LC50: 95.4 mg/l in rats. Test atmosphere: vapor. Method: OECD Test Guideline 403

Skin Corrosion/Irritation: Mild skin irritation in rabbits

Serious Eye Irritation/ Eye Irritation: Mild eye irritation in rabbits. Reversing within 7 days.

Skin Sensitization: No data available

Respiratory Sensitization: No data available

Germ Cell Mutagenicity: Evidence does not support classification of a germ cell mutagen.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Not classified based on available information.

STOT-single exposure: May cause drowsiness and dizziness.

STOT-repeated exposure: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Aspiration toxicity: Not classified based on available information.

Isopropyl Alcohol

Acute Oral Toxicity: LD50, Rat: > 5,000mg/kg
Acute Inhalation Toxicity: 6 hour, LC50, Rat: > 25mg/l (vapor)
Acute Dermal Toxicity: LD50, Rabbit: > 5,000 mg/kg
Skin Corrosion/Irritation: No skin irritation in rabbits
Serious Eye Irritation/ Eye Irritation: Eye irritation, in rabbits. Reversing in 21 days.
Skin Sensitization: Not classified based on available information
Respiratory Sensitization: Not classified based on available information
Germ Cell Mutagenicity: Not classified based on available information
Carcinogenicity: Not classified based on available information.
Reproductive toxicity: Not classified based on available information
STOT-single exposure: May cause drowsiness and dizziness.
STOT-repeated exposure: Not classified based on available information
Aspiration toxicity: Not classified based on available information

12. ECOLOGICAL INFORMATION

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Ecotoxicity: No data available
Persistence and degradability: No data available
Bioaccumulative potential: No data available
Mobility in soil: No data available
Other adverse effects
Results of PBT and vPvB assessment: This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Trans-1,2-Dichloroethylene

96 hour LC50 in Lepomis marochirus (Bluegill sunfish): 135 mg/l
48 hour EC50 in Daphnia magna (Water flea): 220 mg/l
72 hour EC50 in Pseudokirchneriella subcapitata (Green algae): 36.36 mg/l

Biodegradability: Not readily biodegradable. Method: OECD Test Guideline 301D

Isopropyl Alcohol

Ecotoxicity: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Toxic to Fish: 96 hour, LC50 in Fathead minnow (Pimephales promelas): 9640 mg/l
Toxic to daphnia and other aquatic invertebrates: 24 hour, EC50 Water flea (Daphnia magna): >10,000 mg/l
Toxic to microorganisms: 16 hour, EC50 (Pseudomonas putida): >1,050 mg/l
Persistence and degradability: Rapidly degradable
Bioaccumulative potential: Partition coefficient n-octanol/ water (log Pow): 0.05
Mobility in soil: No data available.

13. DISPOSAL CONSIDERATIONS

Comply with federal, state and local regulations. Remove to a permitted waste disposal facility.

14. TRANSPORT INFORMATION

U.S. DOT

Not Regulated

IATA

Not Regulated

IMDG

Not Regulated

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA: All ingredients are listed in TSCA inventory.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (CAS# 138495-42-8) - The United States Environmental Protection Agency has established a Significant New Use Rule (SNUR; 40 CFR 721.5645) for this product. Also, this product requires an export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D.

U.S. State Regulations

California Prop. 65

WARNING: This product can expose you to chemicals including 2,2'-Iminodiethanol, which is/are known to the State of California to cause cancer, and pentadecafluorooctanoic acid, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

NPCA-HMIS Ratings:

Health - 1
Flammability - 1
Reactivity - 1

Personal Protective rating to be supplied by user depending on the conditions.

FOR INDUSTRIAL USE ONLY

REVISION DATE: AUGUST 2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.