

# **Product Information**

www.miller-stephenson.com

# MS-725 / 725M / 727 Heavy Duty Solvent & Flux Remover

## **Description**

A strong cleaning agent containing a Hydrofluoroether azeotrope, ideally suited for removal of rosin, organic flux, oils, grease and waxes. They also can be used for precision and specialty cleaning. Evaporates quickly and leaves no residue. It replaces HCFC-225 in many applications.

#### **ADVANTAGES**

- · Evaporates quickly
- · Leaves no residue
- Non ozone-depleting
- RoHS Compliant

### **PHYSICAL PROPERTIES**

| Boiling Point | 113°F/45°C            |
|---------------|-----------------------|
|               | 450 mmHg              |
|               | 1.22 g/ml @ 70°F/21°Č |
| VOC Content   | -                     |
| Aerosol       | 584 gms / I           |
| Bulk          | 705 gms / I           |

#### PLASTIC COMPATIBILITY

(Immersion: 15 minutes at Room Temperature)

Acetal Polyethylene

Polypropylene Liquid Crystal Polymer

Polyester, PBT, PET Epoxy
Polysulfone, PSO PEK, PEEK
Polyimides PTFE

Phenolic Polyvinylchloride

**NOTE:** Acrylic, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use.

#### **ELASTOMER COMPATIBILITY**

(Immersion: 15 mins at Room Temperature)

Butyl Rubber<sup>1</sup> Natural Rubber
Polysulfide EPDM
Buna S<sup>1</sup> Buna N
Neoprene<sup>1</sup> Urethane
Chlorosuflonated PE Silicone

Fluoroelastomers

Elastomer swelling and shrinking will, in most cases, revert to within a few percent of original size after air drying. Swell, shrinkage, and extractables are strongly affected by the compounding agents, plasticizers, and curing used in the manufacture of the elastomers. Test for compatibility before use.

#### **METAL COMPATIBILTY**

(Immersion: 2 weeks at 248°F/120°C)

Aluminum Copper

Iron

**Note:** Test for compatibility before use.

Safety Data Sheets (SDS) are available upon request.

LIMITATION OF LIABILITY AND REMEDIES: Manufacturer warrants that, at the time of shipment by the Manufacturer, this product is free from defect in material and manufacture. If the product is proved to be defective, the exclusive remedy, at Manufacturer's option, shall be refund of the purchase price or replacement of the defective product, provided written notice of the defect is given no later than one year after the date of shipment by the Manufacturer. Manufacturer shall not otherwise be liable for loss or damages whether direct, indirect, incidental or consequential, regardless of the legal theory asserted, including negligence and strict liability. Manufacturer expressly disclaims all implied warranties, including the implied warranty of merchantability and the implied warranty of fitness for a particular purpose. There are no warranties which extend beyond the description on the face hereof.

1475-10

<sup>&</sup>lt;sup>1</sup>Swelling, but with low extractables.