



Product Information

www.miller-stephenson.com

TriboSys™ 3203 & 3204 Mechanical Keyboard Lube

TriboSys™ 3203 and TriboSys™ 3204 advanced grade 0 semi-fluid lubricants are specifically utilized on mechanical key switches and stabilizers to optimize acoustic and tactile properties. By using a grade 0 lubricant, the applicator can work with the lubricant as if it is a grease but gets the performance of an oil when spread thinly and uniformly with a brush.

The easy application of the grease, the high performance of the oil, the durability and its non-migrating properties results in the protection and even wear of the key switches. The inert properties of the greases will prevent shortening within the controller of the mechanical keyboard. The greases make new mechanical keyboards feel broken in due to normalizing the molding imperfections that occur during the manufacturing process of the switches. This broken-in feeling is a result of the elimination of undesirable acoustic and tactile properties such as a scratching sound and spring jitter.

TriboSys™ 3203

This grease utilizes the least viscous base oil thickened to a grade 0 semi-fluid grease. It is the easiest to work with and it is the ideal lubricant for tactile and click switches.

TriboSys™ 3204

This grease utilizes a higher base viscosity oil thickened to a grade 0 semi-fluid grease. Due to its higher viscosity base oil, it is used for tactile and linear switches. It is recommended for novice users that may not be familiar with how to lubricate a linear switch.

Benefits:

- Easily applied with a brush
- Extremely stable and durable; will act as a lube for life
- Non-migrating; will not create a short
- Grade 0 lubes have the performance of an oil with the ease of application of a grease.

Physical Properties:

Product	3203	3204
Viscosity of the Base Oil cSt @ 20°C (68°F)	82	177
Consistency of Grade 0 ASTM Worked Penetration mm/10 @ 25°C (77°F)	355-385	355-385

LIMITATION OF LIABILITY AND REMEDIES: Manufacturer warrants that, at the time of shipment by the Manufacturer, this product is free from defect in material and manufacture. If the product is proved to be defective, the exclusive remedy, at Manufacturer's option, shall be refund of the purchase price or replacement of the defective product, provided written notice of the defect is given no later than one year after the date of shipment by the Manufacturer. Manufacturer shall not otherwise be liable for loss or damages whether direct, indirect, incidental or consequential, regardless of the legal theory asserted, including negligence and strict liability. **Manufacturer expressly disclaims all implied warranties, including the implied warranty of merchantability and the implied warranty of fitness for a particular purpose. There are no warranties which extend beyond the description on the face hereof.**

1719-110

For technical information call 800.992.2424 or 203.743.4447
For product sales: CT 800.442.3424, CA 800.771.8161
www.miller-stephenson.com

miller-stephenson logo and TriboSys™ are trademarks of Miller-Stephenson Chemical Company Inc