

## SAFETY DATA SHEET

### FOR INDUSTRIAL USE ONLY

### **EPONTM** Resin 164

## Section 1. Product and company identification

**GHS product identifier** : EPON<sup>TM</sup> Resin 164

MSDS Number : K8127 Product type : Epoxy Resin

Material uses : Epoxy Resin Systems

Manufacturer/Supplier/Impor : Hexion Inc.

er 180 East Broad Street

Columbus, Ohio 43215 USA

Contact person : service@hexion.com

**Telephone** : For additional health and safety or regulatory information, call

1 888 443 9466.

**Emergency telephone number** : For Emergency Medical Assistance

Call Health & Safety Information Services

1-866-303-6949

For Emergency Transportation Information CHEMTREC US Domestic (800) 424-9300 CHEMTREC International (703) 527-3887 CANUTEC CA Domestic (613) 996-6666

## Section 2. Hazards identification

Classification of the substance or

mixture

: SKIN CORROSION/IRRITATION - Category 2

SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A

SKIN SENSITISATION - Category 1

**GHS** label elements

Hazard pictograms

**(!**>

Signal word : Dange

**Hazard statements**: H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

### **Precautionary statements**

EPONTM Resin 164 Page:2/13

Not applicable. General

**Prevention** Wear protective gloves.

Wear eye or face protection.

Do not breathe dust.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the

workplace.

Get medical attention if you feel unwell. Response

IF ON SKIN:

Wash with plenty of soap and water. Take off contaminated clothing.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs:

Get medical attention.

IF IN EYES:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

Storage Not applicable.

Dispose of contents and container in accordance with all local, **Disposal** 

regional, national and international regulations.

Other hazards which do not result in classification

Unclassified Hazard - Combustible Dust

Combustible dust when finely divided and suspended in air. Fine dust clouds may form explosive mixtures with air. Product can explode if

dust cloud is formed and ignited.

Minimize airborne dust. Eliminate all fire/ignition sources including static discharges near product/package. Prevent dust accumulation. Refer to Handling Section 7 of the MSDS for more information.

Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

## Section 3. Composition/information on ingredients

Substance/mixture Mixture

Ingredient name	% by weight	CAS number
Formaldehyde, polymer with (chloromethyl)oxirane and methylphenol	100	37382-79-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require

Date of previous issue: 02/26/2015 Version: 14.1 Date of issue/Date of revision: 12/30/2020

EPONTM Resin 164 Page:3/13

reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, the belt or waisthand.

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Wash with plenty of soap and water. Remove contaminated clothing

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

**Ingestion**: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first aid personnel** : No action shall be taken involving any personal risk or without

suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### **Section 5. Fire-fighting measures**

#### Extinguishing media

**Suitable extinguishing media** : Use water spray or mist, dry chemical, foam or CO2.

EPONTM Resin 164 Page:4/13

Unsuitable extinguishing media

Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

Combustible solid that burns. Fine dust clouds may form explosive mixtures with air.

: Decomposition products may include the following materials: carbon oxides halogenated compounds

Special protective actions for fire-fighters

Special protective equipment for fire-fighters

For non-emergency personnel

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Minimize airborne dust and eliminate all fire/ignition sources. Clean up spill as soon as possible using procedures described below. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

Small spill

: Move containers from spill area. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid creating dusty conditions and prevent wind dispersal. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

EPONTM Resin 164 Page: 5/13

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

### COMBUSTIBLE DUST HANDLING PROCEDURES:

Combustible dusts at sufficient concentrations can form explosive mixtures with air. High dust concentrations should be avoided. Follow US NFPA Standard 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids," UK HSE Guidance HSG 103, approved Codes of Practice (ACOPS) established for Explosive Atmospheres under the ATEX Directive 1999/92/EC for worker protection and ATEX Directive 94/9/EC that regulates equipment and protection systems used in potentially explosive atmospheres or other national guidance on safe handling of combustible dusts. Train workers in the recognition and prevention of hazards associated with combustible dust in the plant.

Minimize airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. Use continuous suction at points of dust generation to capture and minimize the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimize the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.

Control sources of static electricity. This product or the package itself can accumulate static charges, and static discharge can be a source of ignition. Solids handling systems must be designed in accordance with applicable NFPA standards (including 654 and 77) and other national guidance. Do not empty directly into flammable solvents or in the presence of flammable vapors. The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of

EPONTM Resin 164 Page:6/13

# Advice on general occupational hygiene

static charges.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# Conditions for safe storage, including any incompatibilities

Eliminate all ignition sources. Separate from oxidising materials. Keep away from heat, hot surfaces, sparks and flame. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

### Occupational exposure limits

Ingredient name	Exposure limits
Formaldehyde, polymer with (chloromethyl)oxirane and methylphenol	None.
Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to

**Appropriate engineering controls** 

hazardous substances will also be required.

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

national guidance documents for methods for the determination of

### **Environmental exposure controls**

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### **Individual protection measures**

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

EPONTM Resin 164 Page: 7/13

### **Eye/face protection**

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

### Skin protection

**Hand protection** 

chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product., For PPE selection see National Fire Protection Association (NFPA) 2113, Standard on Selection, Care, Use and Maintenance of Flame-Resistant Garments for Protection of Industrial Personnel Against Flash Fire.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

### **Appearance**

**Physical state** : Flakes.

Color : Reddish-brown

Odor : Odorless/Odourless
Odor threshold : Not available
pH : Not available
Melting point/ Freezing point : 82 °C (180 °F)

**Boiling point** : Not available

Flash point : Not defined for solids

Burning time:Not availableBurning rate:Not availableEvaporation rate:Not availableFlammability (solid, gas):Not available

**Lower and upper explosive** : **Lower:** Not defined for solids (See MEC)

(flammable) limits Upper: Not defined for solids

EPONTM Resin 164

Page: 8/13

Vapor pressure : Negligible

Vapor density: Not availableRelative density: Not availableSolubility: Not availableSolubility in water: Negligible

**Partition coefficient: n-** : Not available

octanol/water

Auto-ignition temperature:Not availableDecomposition temperature:Not availableSADT:Not available

Viscosity : Dynamic: Not available

Kinematic: Not available

### Other information

\*Minimum Explosive : 0.015 - 0.100 kg/m3(typical range)

**Concentration (MEC)** 

\*Minimum Ignition Energy (MIE) : 3 - 150 mJ (typical range) \*Minimum Ignition Temperature : 490 - 550 °C (typical range)

(MIT)

\*Minimum Ignition Temperature : Not available

- Layer

\*Kst : 43 - 243 m.b\_/s(typical range)
\*Pmax : 90 - 128 psi(typical range)

## Section 10. Stability and reactivity

**Reactivity** : Stable under normal conditions.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions : Hazardous reactions or instability may occur under certain conditions

of storage or use.

**Conditions to avoid** : Avoid the creation of dust when handling and avoid all possible

sources of ignition (spark or flame). Prevent dust accumulation. See

Section 7 Handling.

**Incompatible materials**: Reactive or incompatible with the following materials:

oxidising materials

acids

**Hazardous decomposition products**: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

## Section 11. Toxicological information

<sup>\*</sup> These values listed above are only representative values. A resin's characteristics may change depending upon the process and conditions of use at your facility or any changes made to the resin during use, including further grinding or mixing with other products. In order to obtain more specific data for your particular resin as it is used at your facility, we recommend that you conduct your own characterization testing.

EPONTM Resin 164

Page: 9/13

### **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Formaldehyde, polymer with (chloromethyl)oxirane and methylphenol				
	LD50 Oral	Rat	> 10,000 mg/kg	-
	LD50 Dermal	Rabbit	> 10,000 mg/kg	-

Conclusion/Summary : Not available

**Irritation/Corrosion** 

Conclusion/Summary

Skin:Not availableeyes:Not availableRespiratory:Not available

**Sensitization** 

**Conclusion/Summary** 

Skin : Not available
Respiratory : Not available

**Mutagenicity** 

Conclusion/Summary : Not available

**Carcinogenicity** 

Conclusion/Summary : Not available

**Reproductive toxicity** 

Conclusion/Summary : Not available

**Teratogenicity** 

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Not available

Specific target organ toxicity (repeated exposure)

Not available

**Aspiration hazard** 

Not available

Information on likely routes of

exposure

Not available

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

EPONTM Resin 164 Page: 10/13

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Causes skin irritation. May cause an allergic skin reaction.

**Ingestion**: Irritating to mouth, throat and stomach.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact**: Adverse symptoms may include the following:

pain or irritation

watering redness

**Inhalation** : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

**Ingestion** : No specific data.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

### **Short term exposure**

Potential immediate effects: Not availablePotential delayed effects: Not available

### Long term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

### Potential chronic health effects

Conclusion/Summary : Not available

General : Causes damage to organs through prolonged or repeated exposure:

Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

#### Numerical measures of toxicity

### **Acute toxicity estimates**

No data available.

## **Section 12. Ecological information**

### **Toxicity**

Conclusion/Summary : Not available

EPONTM Resin 164 Page: 11/13

### Persistence/degradability

Conclusion/Summary : Not available

### **Bioaccumulative potential**

Not available

### **Mobility in soil**

Soil/water partition coefficient

(KOC)

: Not available

Other adverse effects

No known significant effects or critical hazards.

### Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **Section 14. Transport information**

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

### **International transport regulations**

Regulatory UN/NA Proper shipping name Classes/\*PG Reportable information number Quantity (RQ)

CFR Non-regulated

TDG Non-regulated

IMO/IMDG Non-regulated

IATA (Cargo) Non-regulated

\*PG: Packing group

**Special precautions for user**: Transport within user's premises: always transport in closed

EPONTM Resin 164 Page: 12/13

containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## **Section 15. Regulatory information**

### **United States**

U.S. Federal regulations

: United States - TSCA 12(b) - Chemical export notification: None required.

United States - TSCA  $5\alpha 2$  - Final significant new use rules: Not listed United States - TSCA  $5\alpha 2$  - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed SARA 311/312 Classification - Immediate (acute) health hazard, Delayed (chronic) health hazard

### California Prop. 65:

WARNING: This product may contain one or more chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

**United States inventory (TSCA**: All components are active or exempted. **8b**)

### **International regulations**

#### **International lists**

: Australia inventory (AICS): All components are listed or exempted.

**Canada inventory:** All components are listed or exempted. **Japan inventory:** All components are listed or exempted.

**China inventory (IECSC):** All components are listed or exempted. **Korea inventory (KECI):** All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): Not determined.

United States inventory (TSCA 8b): All components are active or exempted.

Taiwan inventory (TCSI): All components are listed or exempted.

### **Section 16. Other information**

Hazardous Material Information System III (U.S.A.):

======================================		
Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material. For more information on HMIS®

EPONTM Resin 164 Page: 13/13

### Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**Full text of abbreviated H** : Not applicable.

statements

### **History**

Date of printing: 03/09/2021Date of issue/Date of revision: 12/30/2020Date of previous issue: 02/26/2015Version: 14.1

Prepared by

Key to abbreviations

: Product Safety Stewardship

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

UN = United Nations

**References** : Not available

### Notice to reader

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. HEXION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.

<sup>®</sup> and ™ Licensed trademarks of Hexion Inc.