

MS-530N/532N Contact Re-Nu®

Description:

A cleaning agent that restores electrical or mechanical continuity on all types of contacts. Excellent for cleaning oxides, oil, grease and dust from contacts, switches, relays, tuners, encoders, slide wires, rheostats, distribution panels and servomechanisms. Evaporates quickly and leaves no residue.

Advantages:

- High effective cleaning agent
- Evaporates quickly
- Nonflammable
- Leaves no residue
- RoHS2 and RoHS3 compliant

Typical Properties:

Boiling Point (MS-532N)	131°F /55°C
Liquid Density	1.26 g/ml @ 77°F/25°C
Ozone Depletion	0.00
VOC Content	
Aerosol (MS-530N)	420g/l
Bulk (MS-532N)	372g/l

Plastic Compatibility:

(Immersion: 15 minutes at Room Temperature)

- Acetal
- Polypropylene
- PEK, PEEK
- Polyimides
- PTFE
- Polyethylene
- Polyester, PBT, PET
- Epoxy-Phenolics
- Polyvinylchloride
- Liq. Crystal Polymer

NOTE: Acrylics, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use.

Elastomer Compatibility:

(Immersion: 15 mins at Room Temperature)

- Butyl Rubber
- Polysulfide
- Buna S
- Neoprene
- Chlorosulfonated PE
- Viton™
- Natural Rubber
- EPDM
- Buna N
- Urethane
- Silicone

NOTE: Elastomer swelling and shrinking will, in most cases, revert to within a few percent of original size after air drying. Swell, shrinkage, and extractables are strongly affected by the compounding agents, plasticizers, and curing used in the manufacture of the elastomers. Test for compatibility before use.

Metal Compatibility:

(Immersion: 2 weeks at 99°F/37°C)

- Aluminum
- Copper
- Iron

Note: Test for compatibility before use.

Safety Data Sheets (SDS) are available upon request

Viton™ is a trademark of The Chemours Company FC, LLC

LIMITATION OF LIABILITY AND REMEDIES: Manufacturer warrants that, at the time of shipment by the Manufacturer, this product is free from defect in material and manufacture. If the product is proved to be defective, the exclusive remedy, at Manufacturer's option, shall be refund of the purchase price or replacement of the defective product, provided written notice of the defect is given no later than one year after the date of shipment by the Manufacturer. Manufacturer shall not otherwise be liable for loss or damages whether direct, indirect, incidental or consequential, regardless of the legal theory asserted, including negligence and strict liability. **Manufacturer expressly disclaims all implied warranties, including the implied warranty of merchantability and the implied warranty of fitness for a particular purpose. There are no warranties which extend beyond the description on the face hereof.**