

1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: MS-538N
DPMS-N0622A-2
Contact Re-Nu & Lube

Product Use: Electrical Contact Lubricant

MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical
55 Backus Ave
Danbury, Conn. 06810 USA
(203) 743-4447

Emergency Phone Number:
(800) 424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

Serious Eye Damage/Irritation: Category 2B
Specific Target Organ Toxicity (single exposure): Category 3.

Label elements:

Signal word

Warning

Pictogram



Hazard Statements

Causes serious eye irritation.
May cause drowsiness or dizziness.

Prevention Statements

Do not pierce or burn, even after use.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/ physician if you feel unwell
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/ container to an approved waste disposal plant.

Other Hazards

In use, may form flammable/explosive vapor-air mixture. Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Prolonged skin contact may defat the skin and produce dermatitis or frostbite. Misuse or intentional inhalation abuse may lead to death without warning symptoms, due to cardiac effects.

3. INGREDIENTS

<u>Material (s)</u>	<u>CAS No.</u>	<u>Approximate %</u>
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	138495-42-8	20 – 28
Trans,1,2-Dichloroethylene	156-60-5	40 – 60
Isopropyl Alcohol	67-63-0	4 – 8
Hydrocarbon Lubricant	68649-12-7	< 1
1,1,1,2-Tetrafluoroethane	811-97-2	18 - 22

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air. Get medical attention if symptoms occur.

Eye: Immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Continue to rinse. Get medical attention.

Skin: Immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before use. Thoroughly clean shoes before reuse. Get medical attention.

Oral: DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed: May cause cardiac arrhythmia.

Skin contact may provoke the following symptoms: Dermatitis, Discomfort, Pain, Superficial burning sensation, Redness, Rash, Itching, Swelling of tissue, Irritation

Eye contact may provoke the following symptoms: Pain, Tearing, Swelling of tissue, Redness, Impairment of vision

Inhalation may provoke the following symptoms: Unconsciousness, Drowsiness, Lack of coordination, confusion, Dizziness, Central nervous system depression

Effects of breathing high concentrations of vapor may include: Tiredness, Drowsiness, Central nervous system effects, Convulsions

Adverse effects from repeated inhalation may include central nervous system effects

Aspiration may cause pulmonary edema and pneumonitis. Causes eye irritation. May cause drowsiness or dizziness.

Notes to Physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Flammability: This product is not flammable. **Test Method:** Ignition distance test and Enclosed space ignition test

Suitable Extinguishing Media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO2)

Unsuitable extinguishing media: None known.

Special hazards: Fire or intense heat may cause violent rupture of packages. The product is not flammable. Vapors may form flammable mixture with air. Hazardous combustion products: Hydrogen fluoride, Fluorinated hydrocarbons, Carbonyl fluoride, Carbon oxides, Chlorine compounds.

Special Fire Fighting Instruction: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Evacuate personnel to safe area. Ventilate area. Use personal protective equipment.

Environmental precautions: Prevent material from entering sewers, waterways, or low areas. Should not be released into the environment. Do not allow contact with soil, surface or ground water.

Spill Cleanup: Contain spillage, and then collect with inert absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

7. HANDLING AND STORAGE

Handling: Use in a well-ventilated area to avoid breathing vapors. Use only with adequate ventilation. Use appropriate respiratory protection when ventilations is inadequate. When using do not eat, drink, or smoke. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling.

Storage Conditions: Store in a clean, dry area. Do not store sources of heat, in direct sunlight or where temperatures exceed 120F/49C. Do not pierce or burn, even after use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

ACGIH

OSHA

1,1,1,2,2,3,4,5,5,5-Decafluoropentane	Not Established	Not Established
Trans,1,2-Dichloroethylene	200 ppm, TWA	200 ppm, 8 Hr. TWA
Isopropyl Alcohol	400 ppm, STEL	400 ppm, 8 Hr. TWA
1,1,1,2-Tetrafluoroethane	Not Established	Not Established

Respiratory Protection: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Use gloves impervious to this material when prolonged or frequently repeated contact occurs. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N.A.

Percent Volatile by Volume: 99

Density: 1.26 g/cc @ 77°F/25°C

Vapor Pressure: 302 mmHg @ 77°F/25°C

Vapor Density (Air=1): N.A.

Solubility in H₂O: N.A.

pH Information: Neutral

Evaporation Rate (CC14=1): N.A.

Form: Aerosol

Appearance: Clear & Colorless

Color: Colorless

Odor: Alcohol

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Vapors may form flammable mixture with air. In use may form flammable/explosive vapor-air mixture.

Material and Conditions to Avoid: None known.

Decomposition: No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

1,1,1,2,2,3,4,5,5-Decafluoropentane

Information on likely routes of exposure: Inhalation, Skin contact, Ingestion, Eye contact

Acute Oral: LD50: > 5000 mg/kg in rats

Acute Inhalation (vapor): 4 hour LC50: 114 mg/l in rats

Acute Dermal: LD50: > 5000 mg/kg in rats

Skin Corrosion/Irritation: No skin irritation in rabbits.

Serious Eye Irritation/ Eye Irritation: No eye irritation in rabbits.

Skin Sensitization: No skin sensitization in Guinea pigs.

Respiratory Sensitization: Not classified based on available information.

Germ Cell Mutagenicity: Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Weight of evidence does not support classification as a germ cell mutagen.

STOT-single exposure: Not classified based on available information.

STOT-repeated exposure: No significant health effects observed in animals at concentrations of 1mg/l/6h/d or less.

Aspiration toxicity: Not classified based on available information.

Trans-1,2-Dichloroethylene

Acute Oral: LD50: 7902 mg/kg in rats. Method: OECD Test Guideline 420

Acute Dermal: LD50: > 5,000 mg/kg in rabbits. Method: OECD Test Guideline 402

Acute Inhalation: 4 hour LC50: 95.5 mg/l in rats. Test atmosphere: vapor. Method: OECD Test Guideline 403

Skin Corrosion/Irritation: Mild skin irritation in rabbits. Method: OECD Test Guideline 404

Serious Eye Irritation/ Eye Irritation: Eye irritation in rabbits. Reversing within 7 days. Method: OECD Test Guideline 405

Skin Sensitization: Not classified based on available information.

Respiratory Sensitization: Not classified based on available information.

Germ Cell Mutagenicity: In vitro and In vivo – Not Mutagenic. Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Embryo-fetal development: Negative in rat by inhalation. Method: OECD Test Guideline 414

STOT-single exposure: May cause drowsiness and dizziness.

STOT-repeated exposure: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less by inhalation.

Aspiration toxicity: Not classified based on available information.

Isopropyl Alcohol

Acute Oral: LD50, Rat, > 5,000 mg/kg

Acute Dermal: LD50, Rabbit, > 5,000 mg/kg

Acute Inhalation (vapor): 6 hour LC50, Rat > 25 mg/l

Skin Corrosion/Irritation: No skin irritation in rabbits.

Serious Eye Damage/Irritation: Irritation to eyes in Rabbits, reversing within 21 days.

Skin Sensitization: Buehler Test (skin contact) is negative in Guinea pig. Method OECD Test Guideline 406

Respiratory Sensitization: Not classified based on available information.

Germ Cell Mutagenicity: In vitro and In vivo - Not Mutagenic

Carcinogenicity: Negative in rats exposed 104 weeks by inhalation (vapor). Method: OECD Test Guideline 451

Reproductive Toxicity: Negative in rats by ingestion based on Two-generation reproduction toxicity study and Embryo-fetal development.

STOT- single exposure: May cause drowsiness or dizziness

STOT- repeated exposure: NOAEL, Rat exposed 104 weeks by inhalation (vapor): 12.5 mg/l

Aspiration toxicity: Not classified based on available information.

12. ECOLOGICAL INFORMATION

1,1,1,2,2,3,4,5,5-Decafluoropentane:

96 hour LC50 in *Oncorhynchus mykiss* (rainbow trout): 13.9 mg/l

96 hour LC50 in *Pimephales promelas* (fathead minnow): 27.2 mg/l

96 hour LC50 in *Danio rerio* (zebra fish): 13 mg/l

48 hour LC50 in *Daphnia magna* (Water flea): 11.7 mg/l

72 hour EC50 in *Pseudokirchneriella subcapitata* (Green algae): >120 mg/l

21 days NOEC in *Daphnia magna* (Water flea): 1.72 mg/l

Biodegradability: Not readily biodegradable.

Bioaccumulative potential: Bioaccumulation is unlikely.

Mobility in soil: No data available

Trans-1,2-Dichloroethylene

96 hour LC50 in Lepomis marochirus (Bluegill sunfish): 135 mg/l. Based on data from similar materials.
48 hour EC50 in Daphnia magna (Water flea): 220 mg/l. Method: EPA-660/3-75-009
72 hour EC50 in Pseudokirchneriella subcapitata (Green algae): 36.36 mg/l. Method: OECD Test Guideline 201

Biodegradability: Not readily biodegradable. Method: OECD Test Guideline 301D
Bioaccumulative potential: Partition coefficient: n-octanol/water: log Pow: 2.06

Isopropyl Alcohol

Toxicity to fish: 96 hour LC50 in Pimephales promelas (fathead minnow): 10,000 mg/l
Toxicity to daphnia and other aquatic invertebrates: 24 hour EC50 in Daphnia magna (water flea): >10,000 mg/l
Toxicity to microorganisms: 16 hour EC50 in Pseudomonas putida: >1,050 mg/l

Persistence and degradability: Rapidly degradable. BOD: 1.19 (BOD5)/COD: 2.23BOD/COD: 53%
Bioaccumulative potential: Partition coefficient: n-octanol/water: log Pow: 0.05
Mobility in soil: No data available.

13. DISPOSAL CONSIDERATIONS

If recycling is not practicable, dispose of in compliance with local regulations. Remove to a permitted waste disposal facility.

14. TRANSPORT INFORMATION

U.S. DOT

Limited Quantity

IATA

Proper Shipping Name: Aerosols, Non-Flammable

Hazard Class: 2.2

Identification No. UN1950

Packing Group: None

IMDG

Proper Shipping Name: Aerosols, Non-Flammable

Hazard Class: 2.2

Identification No. UN1950

Packing Group: None

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA: All ingredients are listed in TSCA inventory.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (CAS# 138495-42-8) - The United States Environmental Protection Agency has established a Significant New Use Rule (SNUR; 40 CFR 721.5645) for this product. This product contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D.

CERCLA Reportable Quantity: Trans-Dichloroethylene, 156-60-5: Component RQ is 1000 lbs.

SARA 304 Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity: This material does not contain any components with a section 302 EHS RQ.

SARA 311/312 Hazards: Serious eye damage or eye irritation. Specific target organ toxicity (single or repeated exposure).

SARA 313: This material contains the following component that is subject to reporting levels established by SARA Title III, Section 313: Isopropyl Alcohol (Propan-2-ol).

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer and/or birth defects or other reproductive harm.

16. OTHER INFORMATION

NPCA-HMIS Ratings:

Health	- 1
Flammability	- 0
Reactivity	- 0

Personal Protective rating to be supplied by user depending on the conditions.

FOR INDUSTRIAL USE ONLY

REVISION DATE: JANUARY 2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.