

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

SECTION 1. IDENTIFICATION

Product name : Krytox™ GPL 407
Product code : D10347178
SDS-Identcode : 130000024230

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC
Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)
Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)
Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant
Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
---------------	---------	-----------------------

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

Fumes, silica	69012-64-2	>= 1 - < 5
---------------	------------	------------

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Irritation
Shortness of breath
Inhalation may provoke the following symptoms:
Irritation
Shortness of breath
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not applicable
Will not burn
- Unsuitable extinguishing media : Not applicable
Will not burn
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment : Wear self-contained breathing apparatus for firefighting if

SAFETY DATA SHEET



Krytox™ GPL 407

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2022
7.0	11/11/2022	1745395-00013	Date of first issue: 06/14/2017

for fire-fighters : necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not breathe decomposition products.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : No special restrictions on storage with other products.
- Further information on storage stability : No decomposition if stored and applied as directed.
-

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
 Date of first issue: 06/14/2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Fumes, silica	69012-64-2	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL
		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm	OSHA Z-1

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

			55 mg/m ³	
--	--	--	----------------------	--

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Grease

Color : white

Odor : odorless

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : 608 °F / 320 °C

Initial boiling point and boiling : No data available

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

range

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.89 - 1.93

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : 662 °F / 350 °C

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Fumes, silica:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401 Remarks: Based on data from similar materials
Acute inhalation toxicity	:	LC50 (Rat): > 2.08 mg/l Exposure time: 4 h Test atmosphere: dust/mist Remarks: Based on data from similar materials
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Fumes, silica:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Fumes, silica:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Fumes, silica:

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	:	Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Ingestion Result: negative Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Fumes, silica:

Species	:	Rat
Application Route	:	Ingestion
Exposure time	:	103 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Fumes, silica:

Effects on fertility	:	Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion
----------------------	---	---

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Fumes, silica:

Species : Rat
NOAEL : 2,500 mg/kg
Application Route : Ingestion
Exposure time : 103 Weeks
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Fumes, silica:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,003 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Skeletonema costatum (marine diatom)): 4,200 mg/l
Exposure time: 72 h
Method: ISO 10253

EC10 (Skeletonema costatum (marine diatom)): 1,200 mg/l
Exposure time: 72 h
Method: ISO 10253

Toxicity to microorganisms : EC50: 5,000 mg/l
Exposure time: 20 h

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

II

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

PFPE fluid
Fumes, silica

Trade secret
69012-64-2


California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Pentadecafluorooctanoic acid, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

SAFETY DATA SHEET



Krytox™ GPL 407

Version 7.0 Revision Date: 11/11/2022 SDS Number: 1745395-00013 Date of last issue: 04/12/2022
Date of first issue: 06/14/2017

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD

SAFETY DATA SHEET



Krytox™ GPL 407

Version	Revision Date:	SDS Number:	Date of last issue: 04/12/2022
7.0	11/11/2022	1745395-00013	Date of first issue: 06/14/2017

compile the Material Safety
Data Sheet

eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/11/2022

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8