

# SAFETY DATA SHEET

### FOR INDUSTRIAL USE ONLY

### EPON<sup>TM</sup> Resin SU-8

## Section 1. Product and company identification

GHS product identifier MSDS Number Product type Material uses	::	EPON™ Resin SU-8 K9359 Epoxy Resin Epoxy Resin Systems
Manufacturer/Supplier/Importer	:	Westlake Epoxy Inc. 12650 DIRECTORS DR STE 100 Stafford, Texas 77477 USA
Contact person Telephone	:	epoxyservice@westlake.com For additional health and safety or regulatory information, call 1 888 443 9466.
Emergency telephone number	:	For Emergency Medical Assistance Call Health & Safety Information Services 1-866-303-6949 For Emergency Transportation Information NCEC US Domestic +1 866 928 0789 (toll-free, US only) NCEC Americas +1 215 207 0061 CANUTEC CA Domestic (613) 996-6666

## Section 2. Hazards identification

Classification of the substance or mixture	:	SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A SKIN SENSITISATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3 COMBUSTIBLE DUSTS
GHS label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	<ul> <li>H315 Causes skin irritation.</li> <li>H319 Causes serious eye irritation.</li> <li>H317 May cause an allergic skin reaction.</li> <li>H335 May cause respiratory irritation. May form combustible dust concentrations in air.</li> </ul>

Version: 9.0

:	Not applicable.
:	Wear protective gloves. Wear eye or face protection. Use only outdoors or in a well-ventilated area. Avoid breathing dust. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.
:	<ul> <li>IF INHALED:</li> <li>Remove victim to fresh air and keep at rest in a position comfortable for breathing.</li> <li>Call a POISON CENTER or physician if you feel unwell.</li> <li>IF ON SKIN:</li> <li>Wash with plenty of soap and water.</li> <li>Take off contaminated clothing.</li> <li>Wash contaminated clothing before reuse.</li> <li>If skin irritation or rash occurs:</li> <li>Get medical attention.</li> <li>IF IN EYES:</li> <li>Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>If eye irritation persists:</li> <li>Get medical attention.</li> </ul>
:	Store locked up.
:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
:	Combustible dust when finely divided and suspended in air. Fine dust clouds may form explosive mixtures with air. Product can explode if dust cloud is formed and ignited. Minimize airborne dust. Eliminate all fire/ignition sources including static discharges near product/package. Prevent dust accumulation. Refer to Handling Section 7 of the MSDS for more information. Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

## Section 3. Composition/information on ingredients

Substance/mixture

: Substance

CAS number/other identifiers

CAS number EC number : 28906-96-9 Not available

Ingredient name	% by weight	CAS number
Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-	100	28906-96-9
(1-methylethylidene)bis[phenol]		

Any concentration shown as a range is to protect confidentiality or is due to batch variation. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	:	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	:	Treat symptomatically. Contact poison treatment specialist
		immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first aid personnel	:	No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

#### Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media	:	Use water spray or mist, dry chemical, foam or CO2. Do not use water jet.
Specific hazards arising from the chemical Hazardous thermal decomposition products	:	Combustible solid that burns. Fine dust clouds may form explosive mixtures with air. No specific data.
Special protective actions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Minimize airborne dust and eliminate all fire/ignition sources. Clean up spill as soon as possible using procedures described below. Avoid breathing dust. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for containmen	nt and	d cleaning up

Small spill: Move containers from spill area. Do not use air hoses for cleaning.<br/>Minimize dry sweeping to avoid generation of dust clouds. Vacuum<br/>dust-accumulating surfaces and remove to a chemical disposal area.<br/>Use spark-proof tools and explosion-proof equipment. Vacuums with

	waste disposal contractor.
Large spill	: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid creating dusty conditions and prevent wind dispersal. Do not use air hoses for cleaning. Minimize dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Use spark-proof tools and explosion-proof equipment. Vacuums with explosion-proof motors should be used. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

### Section 7. Handling and storage

:

#### Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

explosion-proof motors should be used. Dispose of via a licensed

#### COMBUSTIBLE DUST HANDLING PROCEDURES:

Combustible dusts at sufficient concentrations can form explosive mixtures with air. High dust concentrations should be avoided. Follow US NFPA Standard 654, "Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids," UK HSE Guidance HSG 103, approved Codes of Practice (ACOPS) established for Explosive Atmospheres under the ATEX Directive 1999/92/EC for worker protection and ATEX Directive 94/9/EC that regulates equipment and protection systems used in potentially explosive atmospheres or other national guidance on safe handling of combustible dusts. Train workers in the recognition and prevention of hazards associated with combustible dust in the plant.

Minimize airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. Use continuous suction at points of dust generation to capture and minimize the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimize the

		probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area.
		Control sources of static electricity. This product or the package itself can accumulate static charges, and static discharge can be a source of ignition. Solids handling systems must be designed in accordance with applicable NFPA standards (including 654 and 77) and other national guidance. Do not empty directly into flammable solvents or in the presence of flammable vapors. The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep away from heat, hot surfaces, sparks and flame. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

### Control parameters

### **Occupational** exposure limits

Ingredient name	Exposure limits
Formaldehyde, polymer with (chloromethyl)oxirane and 4,4'-(1- methylethylidene)bis[phenol]	None.
Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls :	Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls :	Emissions from ventilation or work process equipment should be

	protection legislation. In some	y with the requirements of environmental e cases, fume scrubbers, filters or the process equipment will be necessary able levels.
Individual protection measures		
Hygiene measures	products, before eating, smoki of the working period. Approp remove potentially contaminat clothing should not be allowed contaminated clothing before and safety showers are close to	reusing. Ensure that eyewash stations o the workstation location.
Eye/face protection	when a risk assessment indica liquid splashes, mists, gases o	th an approved standard should be used tes this is necessary to avoid exposure to r dusts. If contact is possible, the e worn, unless the assessment indicates a hemical splash goggles.
Skin protection		
Hand protection	standard should be worn at all if a risk assessment indicates to parameters specified by the gl the gloves are still retaining the noted that the time to breakther different for different glove m	s gloves complying with an approved times when handling chemical products this is necessary. Considering the ove manufacturer, check during use that heir protective properties. It should be rough for any glove material may be anufacturers. In the case of mixtures, tes, the protection time of the gloves
Body protection	Personal protective equipment on the task being performed a approved by a specialist befor selection see National Fire Pro Standard on Selection, Care, U	t for the body should be selected based nd the risks involved and should be e handling this product., For PPE otection Association (NFPA) 2113, Use and Maintenance of Flame-Resistant dustrial Personnel Against Flash Fire.
Other skin protection	Appropriate footwear and any should be selected based on the	additional skin protection measures task being performed and the risks wed by a specialist before handling this
Respiratory protection	Use a properly fitted, particula approved standard if a risk ass Respirator selection must be b	ate filter respirator complying with an sessment indicates this is necessary. based on known or anticipated exposure fuct and the safe working limits of the

# Section 9. Physical and chemical properties

### **Appearance**

Physical state Color		Flakes. Amber.
Odor	:	Not available

Odor threshold	:	Not available
pН	:	Not available
Melting point/ Freezing point	:	83 °C (181 °F)
Boiling point	:	Not available
Flash point	:	Not defined for solids
Burning time	:	Not available
Burning rate	:	Not available
Evaporation rate	:	Not available
Flammability (solid, gas)	:	Not available
Lower and upper explosive	:	Lower: Not defined for solids (See MEC)
(flammable) limits		<b>Upper:</b> Not defined for solids
Vapor pressure	:	Less than 0.13 mbar @ 20 °C (68 °F)
Vapor density	:	Not available
Relative density	-	1.2
Density	:	1,200 kg/m3
Solubility	:	Not available
Solubility in water	:	Negligible
Partition coefficient: n- octanol/water	:	Not available
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
SADT	:	Not available
Viscosity	:	<b>Dynamic:</b> Not available
		Kinematic: Not available
Other information		
*Minimum Explosive	:	15 - 100 kg/m3(typical range)
Concentration (MEC)		
*Minimum Ignition Energy (MIE)	:	3 - 150 mJ (typical range)
*Minimum Ignition Temperature	:	490 - 550 °C (typical range)
(MIT)		
*Minimum Ignition Temperature	:	Not available
- Layer		
*Kst	:	43 - 243 m.b_/s(typical range)
*Pmax	:	349 - 427 psi(typical range)

\* These values listed above are only representative values. A resin's characteristics may change depending upon the process and conditions of use at your facility or any changes made to the resin during use, including further grinding or mixing with other products. In order to obtain more specific data for your particular resin as it is used at your facility, we recommend that you conduct your own characterization testing.

### Section 10. Stability and reactivity

#### Reactivity

: Stable under normal conditions.

Chemical stability

: The product is stable.

Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	:	Avoid the creation of dust when handling and avoid all possible sources of ignition (spark or flame). Prevent dust accumulation. See Section 7 Handling.
Incompatible materials	:	Reactive or incompatible with the following materials: oxidising materials acids
Hazardous decomposition products	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Other hazards		Polymerises exothermically with amines, mercaptans and Lewis acids at ambient temperature and above.

## Section 11. Toxicological information

### Information on toxicological effects

Acute toxicity		
Conclusion/Summary	:	Not available
Irritation/Corrosion		
Conclusion/Summary Skin	:	Not available
eyes	:	Not available
Respiratory	:	Not available
Sensitization		
Conclusion/Summary Skin	:	Not available
Respiratory	:	Not available
<u>Mutagenicity</u>		
Conclusion/Summary	:	Not available
<b>Carcinogenicity</b>		
Conclusion/Summary	:	Not available
<u>Reproductive toxicity</u>		
Conclusion/Summary	:	Not available
<b>Teratogenicity</b>		
Conclusion/Summary	:	Not available

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs	
Formaldehyde, polymer with 2- (chloromethyl)oxirane and 4,4'-(1-	Category 3	-	Respiratory tract irritation	
methylethylidene)bis[phenol]				
Specific target organ toxicity (re Not available	<u>peated exposure)</u>			
Aspiration hazard Not available				
Information on likely routes of exposure	: Not available			
Potential acute health effects				
Eye contact	: Causes seriou	s eye irritation.		
Inhalation		spiratory irritation.		
Skin contact		ritation. May cause an alle	rgic skin reaction.	
Ingestion	: Irritating to m	outh, throat and stomach.		
Symptoms related to the physical,	chemical and toxicolo	gical characteristics		
Eye contact	: Adverse sym pain or irritati watering redness	ptoms may include the follon	owing:	
Inhalation	: Adverse sym respiratory tra coughing		-	
Skin contact	: Adverse symptoms may include the following: irritation redness			
Ingestion	: No specific d	ata.		
Delayed and immediate effects as	well as chronic effects	from short and long-tern	<u>n exposure</u>	
Short term exposure				
Potential immediate effects Potential delayed effects	<ul><li>Not available</li><li>Not available</li></ul>			
Long_term exposure				
Potential immediate effects Potential delayed effects	<ul><li>Not available</li><li>Not available</li></ul>			
Potential chronic health effects				
Conclusion/Summary	: Not available			
General		ed, a severe allergic reaction exposed to very low levels		

Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Teratogenicity	:	No known significant effects or critical hazards.
Developmental effects	:	No known significant effects or critical hazards.
Fertility effects	:	No known significant effects or critical hazards.

Numerical measures of toxicity

### Acute toxicity estimates

No data available.

## Section 12. Ecological information

### **Toxicity**

Conclusion/Summary	:	Not available
Persistence/degradability		
Conclusion/Summary	:	Not available
Bioaccumulative potential Not available Mobility in soil		
Soil/water partition coefficient	:	Not available
(KOC) Other adverse effects	:	No known significant effects or critical hazards.

## Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever **Disposal methods** : possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

International transport regul	ations			
Regulatory UN/NA information number	Proper shi	pping name	Classes/*PG	Reportable Quantity (RQ)
CFR	Non-regulat	ted		
TDG	Non-regulated			
IMO/IMDG	Non-regulated			
IATA (Cargo)	Non-regulated			
*PG : Packing group				
Special precautions for user	:	containers that are	ser's premises: always upright and secure. En oduct know what to do	1

### Section 15. Regulatory information

#### United States

U.S. Federal regulations	:	United States - TSCA 12(b) - Chemical export notification: None required.
		<b>United States - TSCA 5α2 - Final significant new use rules:</b> Not listed
		United States - TSCA 5a2 - Proposed significant new use rules: Not
		listed
		United States - TSCA 5(e) - Substances consent order: Not listed
		SARA 311/312 Classification - Immediate (acute) health hazard

#### California Prop. 65:

This product does not require a Safe Harbor warning under California Prop. 65.

United States inventory (TSCA : All components are active or exempted. 8b)

#### International regulations

 

 International lists
 : Australia inventory (AIIC): All components are listed or exempted. Canada inventory: All components are listed or exempted. Japan inventory: All components are listed or exempted. China inventory (IECSC): All components are listed or exempted. Korea inventory (KECI): All components are listed or exempted. New Zealand Inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted.

 United States inventory (TSCA 8b): All components are active or exempted. Taiwan inventory (TCSI): All components are listed or exempted.

### Section 16. Other information

#### Hazardous Material Information System III (U.S.A.) :

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS<sup>®</sup> ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS<sup>®</sup> ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS<sup>®</sup> ratings are to be used with a fully implemented HMIS<sup>®</sup> program. HMIS<sup>®</sup> is a registered mark of the National Paint & Coatings Association (NPCA). HMIS<sup>®</sup> materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material. For more information on HMIS<sup>®</sup> Personal Protective Equipment (PPE) codes, consult the HMIS<sup>®</sup> Implementation Manual.

Full text of abbreviated H statements	:	Not applicable.
History		
Date of printing Date of issue/Date of revision Date of previous issue Version Prepared by Key to abbreviations		10/27/2022 09/22/2022 07/16/2019 9.0 Product Safety Stewardship ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IAT A = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
References	:	Not available

#### Notice to reader

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.