

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

SECTION 1. IDENTIFICATION

Product name : Krytox™ XHT-ACX

Product code : D12434528

SDS-Identcode : 130000031594

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

Components

Chemical name	CAS-No.	Concentration (% w/w)
Sodium nitrite	7632-00-0	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:
Irritation
Lung edema
Eye contact may provoke the following symptoms
Blurred vision
Discomfort
Lachrymation
Skin contact may provoke the following symptoms:
Irritation
Redness
Inhalation may provoke the following symptoms:
Irritation
Shortness of breath
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Not applicable
Will not burn
- Unsuitable extinguishing media : Not applicable
Will not burn
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2023
6.2	11/02/2023	1788895-00015	Date of first issue: 06/26/2017

aerosolized particulates
Carbon oxides
Nitrogen oxides (NOx)
Metal oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride	7664-39-3	TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
		C	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
		TWA	3 ppm	OSHA Z-2
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m ³	NIOSH REL
		ST	5 ppm 15 mg/m ³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
Carbon monoxide	630-08-0	TWA	5,000 ppm 9,000 mg/m ³	OSHA Z-1
		TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m ³	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

		C	200 ppm 229 mg/m ³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Grease

Color : white

Odor : odorless

Odor Threshold : No data available

pH : 7

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2023
6.2	11/02/2023	1788895-00015	Date of first issue: 06/26/2017

Melting point/freezing point : 608 °F / 320 °C

Initial boiling point and boiling range : No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.89 - 1.93

Solubility(ies)
Water solubility : insoluble

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : No data available

Decomposition temperature : 608 °F / 320 °C

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2023
6.2	11/02/2023	1788895-00015	Date of first issue: 06/26/2017

Possibility of hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Sodium nitrite:

Acute oral toxicity : LD50 (Rat): 180 mg/kg

Acute inhalation toxicity : LC50 (Rat): 5.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Components:

Sodium nitrite:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Sodium nitrite:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Sodium nitrite:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Test Type: In vitro mammalian cell gene mutation test
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Sodium nitrite:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

IARC Group 2A: Probably carcinogenic to humans

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

Sodium nitrite 7632-00-0
(nitrite (ingested) under conditions that result in endogenous nitrosation)

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Sodium nitrite:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Mouse
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Sodium nitrite:

Species : Rat
NOAEL : 10 mg/kg
Application Route : Ingestion
Exposure time : 2 y

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Sodium nitrite:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.54 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2023
6.2	11/02/2023	1788895-00015	Date of first issue: 06/26/2017

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 15.4 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Scenedesmus capricornutum (fresh water algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Cyprinus carpio (Carp)): 21 mg/l
Exposure time: 30 d
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Penaeid Shrimp): 9.86 mg/l
Exposure time: 80 d

Toxicity to microorganisms : EC50: 281 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(Sodium nitrite)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : no
Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE
SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS
THE REPORTABLE QUANTITY.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium nitrite	7632-00-0	100	5050

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Sodium nitrite 7632-00-0 >= 1 - < 5 %

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version 6.2 Revision Date: 11/02/2023 SDS Number: 1788895-00015 Date of last issue: 04/03/2023
Date of first issue: 06/26/2017

US State Regulations

Pennsylvania Right To Know

PFPE fluid	Trade secret
Fluoropolymer	Trade secret
Sodium nitrite	7632-00-0

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

California List of Hazardous Substances

Sodium nitrite	7632-00-0
----------------	-----------

Additional regulatory information


Sodium nitrite 7632-00-0

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.
See 40 CFR § 721.4740

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	/	0
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Krytox™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2023
6.2	11/02/2023	1788895-00015	Date of first issue: 06/26/2017

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	:	USA. Occupational Exposure Limits (OSHA) - Table Z-2
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
ACGIH / C	:	Ceiling limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to : Internal technical data, data from raw material SDSs, OECD

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Krytox™ XHT-ACX

Version	Revision Date:	SDS Number:	Date of last issue: 04/03/2023
6.2	11/02/2023	1788895-00015	Date of first issue: 06/26/2017

compile the Material Safety
Data Sheet

eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 11/02/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8