

1. CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Name: MS-555
DPMS-C0716A
Heavy Duty Solvent & Flux Remover

Product Use: Solvent Cleaning & Flux Removal
for electronic assemblies.

MANUFACTURER/DISTRIBUTOR:

Miller-Stephenson Chemical
55 Backus Ave.
Danbury, Conn. 06810 USA
(203) 743-4447

Emergency Phone Number:
(800) 424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

Flammable aerosol: Category 2

Serious Eye Damage/Irritation: Category 2B

Specific Target Organ Toxicity (single exposure): Category 2 (Eye, Central nervous system)

Specific Target Organ Toxicity (single exposure): Category 3

Label elements:

Signal word

Warning

Pictograms



Hazard Statements

Flammable aerosol

Causes eye irritation.

May cause drowsiness and dizziness.

May cause damage to organs (Eye, Central Nervous system).

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe mist/vapors/spray.

Wash skin thoroughly after handling.

Do not eat, drink, or smoke when using this product.

Use only outdoors or in a well-ventilated area.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/ physician, if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/ attention.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/ container in accordance with local, regional, national, and international regulations.

Other Hazards

Flammable aerosol. Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may lead to death without warning symptoms, due to cardiac effects.

3. INGREDIENTS

<u>Material (s)</u>	<u>CAS No.</u>	<u>Approximate %</u>
1,1,1,2,2,3,4,5,5,5-Decafluoropentane	138495-42-8	22 - 26
Trans,1.2-Dichloroethylene	156-60-5	65 - 70
Methanol	67-56-1	4 - 6
Carbon Dioxide	124-38-9	3 - 4

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air. Get medical attention.

Eye: Immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Continue to rinse. Get medical attention.

Skin: Immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before use. Thoroughly clean shoes before reuse. Get medical attention.

Oral: DO NOT induce vomiting. Get medical attention. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed: May cause cardiac arrhythmia.

Skin contact may provoke the following symptoms: Dermatitis, Discomfort, Pain, Redness, Rash, Itching, Swelling of tissue, Eye damage

Eye contact may provoke the following symptoms: Irritation, Pain, Tearing, Swelling of tissue, Redness, Impairment of vision, Discomfort

Inhalation may provoke the following symptoms: Eye damage

Effects of breathing high concentrations of vapor may include: Tiredness, Drowsiness, Central nervous system effects, Convulsions

Adverse effects from repeated inhalation may include central nervous system effects

Ingestion may provoke the following symptoms: Lack of coordination, Narcosis, Eye damage

Aspiration may cause pulmonary edema and pneumonitis.

Causes eye irritation. May cause drowsiness or dizziness. May cause damage to organs.

Notes to Physician: Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

5. FIRE FIGHTING MEASURES

Flammability: This product is flammable. **Test Method:** Ignition distance test and Enclosed space ignition test

Suitable Extinguishing Media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO₂)

Unsuitable extinguishing media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special hazards: Vapors may form explosive mixture with air. Exposure to combustion products may be hazardous to health.

Hazardous combustion products: Hydrogen fluoride, Carbonyl fluoride, Carbon oxides, Chlorine compounds.

Special Fire Fighting Instruction: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Further information: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Evacuate personnel to safe area. Use personal protective equipment. Ventilate area. In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Spill Cleanup: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

7. HANDLING AND STORAGE

Handling: If sufficient ventilation is unavailable, use local exhaust ventilation. Use only in an area equipped with explosion-proof exhaust ventilation, if advised by assessment of the local exposure potential. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink, or smoke. Do not swallow. Avoid contact with skin, eyes, or clothing. Wash thoroughly after handling.

Storage Conditions: Store in a clean, dry place that is well-ventilated. Do not store near sources of heat, in direct sunlight or where temperatures exceed 125°F/52°C. Do not pierce or burn, even after use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

ACGIH

OSHA

1,1,1,2,2,3,3,4,5,5,5-Decafluoropentane
Trans,1,2-Dichloroethylene
Methanol

Not Established
200 ppm, TWA
200 ppm, TWA

Not Established
200 ppm, TWA
200 ppm, TWA

Respiratory Protection: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection

Eye Protection: Avoid eye contact. Use chemical goggles or safety glasses with side shields.

Skin Protection: Avoid contact with skin. Use gloves impervious to this material (eg. Viton) when prolonged or frequently repeated contact occurs. For special applications, we recommend clarifying the resistance to chemicals of the protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: N.A.

Percent Volatile by Volume: 100%

Density: 1.28 g/cc at 77°F/25°C

Vapor Pressure: To be determined

Vapor Density (Air=1): >1

Solubility in H₂O : To be determined

pH Information: Neutral

Evaporation Rate (CC14=1): N.A.

Form: Aerosol

Appearance: Clear

Color: Colorless

Odor: Ethereal

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Vapors form flammable mixture in air. In use may form flammable /explosive vapor-air mixture.

Material and Conditions to Avoid: None known.

Decomposition: No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

1,1,1,2,2,3,4,5,5,5-Decafluoropentane

Information on likely routes of exposure: Inhalation, Skin contact, Ingestion, Eye contact

Acute Oral: LD50: > 5000 mg/kg in rats. Method: OECD Test Guideline 401

Acute Inhalation (vapor): 4 hour LC50: 114.428 mg/l in rats. Method: OECD Test Guideline 403

Acute Dermal: LD50: > 5000 mg/kg in rabbits. Method: OECD Test Guideline 402

Skin Corrosion/Irritation: No skin irritation in rabbits. Method: OECD Test Guideline 404

Serious Eye Irritation/ Eye Irritation: No eye irritation in rabbits. Method: OECD Test Guideline 405

Skin Sensitization: No skin sensitization in Guinea pigs. Buehler Test. Method: OECD Test Guideline 406

Respiratory Sensitization: Not classified based on available information.

Germ Cell Mutagenicity: Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Weight of evidence does not support classification for reproductive toxicity.

STOT-single exposure: Inhalation (vapor): No significant health effects observed in animals at concentrations of 20mg/l/4h or less.

STOT-repeated exposure: Inhalation (vapor): No significant health effects observed in animals at concentrations of 1mg/l/6h/d or less.

Aspiration toxicity: No aspiration toxicity classification.

Trans-1,2-Dichloroethylene

Acute Oral: LD50: 7902 mg/kg in rats. Method: OECD Test Guideline 420

Acute Dermal: LD50: > 5,000 mg/kg in rabbits. Method: OECD Test Guideline 402

Acute Inhalation: 4 hour LC50: 95.5 mg/l in rats. Test atmosphere: vapor. Method: OECD Test Guideline 403

Skin Corrosion/Irritation: Mild skin irritation in rabbits. Method: OECD Test Guideline 404

Serious Eye Irritation/Eye Irritation: Eye irritation in rabbits. Reversing within 7 days. Method: OECD Test Guideline 405

Skin Sensitization: Not classified based on available information.

Respiratory Sensitization: Not classified based on available information.

Germ Cell Mutagenicity: Evidence does not support classification of a germ cell mutagen.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Test Type: Embryo-fetal development. Inhalation in rats. Negative. Method: OECD Test Guideline 414

STOT-single exposure: May cause drowsiness and dizziness.

STOT-repeated exposure: Inhalation: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Aspiration toxicity: Not classified based on available information.

Methanol

Acute Inhalation toxicity: 3mg/l estimated, 4 hours (vapor). Method: Expert judgement. Remarks: Based on national or regional regulation.

Acute Dermal toxicity: 300 mg/kg, (estimated). Method: Expert judgement. Remarks: Based on national or regional regulation.

Acute Oral Toxicity: 300 mg/kg, (estimated in humans), Method: Expert judgement.

Skin Corrosion/Irritation: No irritation, Rabbit

Serious Eye Irritation/ Eye Irritation: No irritation, Rabbit

Skin sensitization: Negative in Guinea pig (Maximization Test)

Respiratory Sensitization: Not classified based on available information.

Germ Cell Mutagenicity: Genotoxicity in vivo and vitro tests were negative.

Carcinogenicity: Negative in Monkey, 7 months (inhalation-vapor).

Reproductive Toxicity:

Effects on fertility: Negative in Monkey (inhalation-vapor). Test Type: One-generation reproduction toxicity study.

Effects on fetal development: Negative in Monkey (inhalation-vapor). Test Type: Reproduction/Development toxicity screening test.

STOT-single exposure: May cause damage to organs (Optic nerve, Central Nervous System)

STOT-repeated exposure: Not classified based on available information.

Aspiration toxicity: Not classified based on available information.

12. ECOLOGICAL INFORMATION

1,1,1,2,2,3,4,5,5,5-Decafluoropentane

96 hour LC50 in Danio rerio (zebra fish): 13 mg/l. Method: OECD Test Guideline 203

48 hour EC50 in Daphnia magna (Water flea): 10.6 mg/l. Method: OECD Test Guideline 202

72 hour EC50 in Selenastrum capricornutum (Green algae): >120 mg/l. Method: OECD Test Guideline 201

21 days NOEC in Daphnia magna (Water flea): 1.72 mg/l. Method: OECD Test Guideline 211

Biodegradability: Not readily biodegradable. Method: OECD Test Guideline 301D

Bioaccumulative potential: Bioaccumulation is unlikely. Partition coefficient: noctanol/water: log Pow: 2.4 (75 °F / 24 °C)

Mobility in soil: No data available

Trans-1,2-Dichloroethylene

96 hour LC50 in Lepomis marochirus (Bluegill sunfish): 135 mg/l. Based on data similar materials

48 hour EC50 in Daphnia magna (Water flea): 220 mg/l. Method: EPA-660/3-75-009

48 hour EbC50 in Pseudokirchneriella subcapitata (Green algae): 36.36 mg/l. Method: OECD Test Guideline 201

Biodegradability: Not readily biodegradable. Method: OECD Test Guideline 301D

Bioaccumulative potential: Partition coefficient: n-octanol/water: log Pow: 2.06

Mobility in soil: No data available

Methanol

96 hour LC50 in Lepomis marochirus (Bluegill sunfish): 15,400 mg/l

48 hour EC50 in Daphnia magna (Water flea): >10,000 mg/l, Method: DIN 38412

96 hour ErC50 in Raphidocelis subcapitata (freshwater green algae): 22,000 mg/l. Method: OECD Test Guideline 201

3 hour EC50 in activated sludge: > 1,000 mg/l. Test substance: Neutralized product. Method: OECD Test Guideline 209

Biodegradability: Readily biodegradable. 95% biodegradable in 20 days

Bioaccumulative potential: Bioconcentration factor (BCF): <10 in Leuciscus idus (Golden orfe). Partition coefficient: n-octanol/water: log Pow: -0.77

13. DISPOSAL CONSIDERATIONS

If recycling is not practicable, dispose of in compliance with local regulations. Remove to a permitted waste disposal facility.

14. TRANSPORT INFORMATION

U.S. DOT

Limited Quantity

IATA

Proper Shipping Name: Aerosols, Flammable

Hazard Class: 2.1

Identification No. UN1950

Packing Group: None

IMDG

Proper Shipping Name: Aerosols, Flammable

Hazard Class: 2.1

Identification No. UN1950

Packing Group: None

15. REGULATORY INFORMATION

U.S. Federal Regulations

TSCA: All ingredients are listed in TSCA inventory.

1,1,1,2,2,3,4,5,5,5-Decafluoropentane (CAS# 138495-42-8) - The United States Environmental Protection Agency has established a Significant New Use Rule (SNUR; 40 CFR 721.5645) for this component in this product. This product contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D.

CERCLA Reportable Quantity: Methanol, 67-56-1: Component RQ is 5000 lbs. Trans-Dichloroethylene, 156-60-5: Component RQ is 1000 lbs.

SARA 304 Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity: This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards: Serious eye damage or eye irritation. Specific target organ toxicity (single or repeated exposure)

SARA 313: Methanol is subject to reporting levels established by SARA Title III, Section 313.

California Proposition 65: This product contains Methanol which is known to the state of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

16. OTHER INFORMATION

NPCA-HMIS Ratings:

Health - 2

Flammability - 2

Reactivity - 0

Personal Protective rating to be supplied by user depending on the conditions.

FOR INDUSTRIAL USE ONLY

REVISION DATE: MAY 30, 2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.