according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/02/2023

 1.1
 10/24/2024
 11290755-00002
 Date of first issue: 11/02/2023

SECTION 1. IDENTIFICATION

Product name : Krytox™ Anti-Rust 4578

Product code : D15445174

SDS-Identcode : 130000150962

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : For industrial use only.

Do not use or resell Chemours[™] materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information,

please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

Other hazards

The thermal decomposition vapors of fluorinated plastics may cause polymer fume fever with flulike symptoms in humans, especially when smoking contaminated tobacco.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

Components

Chemical name	CAS-No.	Concentration (% w/w)
1,1,1,2,2,3,4,5,5,5-	138495-42-8	>= 30 - < 50
Decafluoropentane		
Poly(oxy <trifluoro(trifluoromethyl)ethy lene="">), omega-fluoro-alpha- <tetrafluoro-1 <<(hydroxyphenoxy-<br="">phosphinyl)oxy>methyl>ethyl>-</tetrafluoro-1></trifluoro(trifluoromethyl)ethy>	Not Assigned	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

and effects, both acute and

delayed

Inhalation may provoke the following symptoms:

Irritation

Shortness of breath

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Hydrogen fluoride carbonyl fluoride

Carbon oxides

potentially toxic fluorinated compounds

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

aerosolized particulates

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions : Av

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure as-

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Do not breathe decomposition products.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
1,1,1,2,2,3,4,5,5,5-	138495-42-8	TWA	225 ppm	WEEL
Decafluoropentane			2,320 mg/m ³	
		STEL	700 ppm	WEEL
			7,217 mg/m ³	

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hydrogen fluoride 7664-39-3 TWA C		TWA	0.5 ppm (Fluorine)	ACGIH
		С	2 ppm (Fluorine)	ACGIH
		TWA	3 ppm	OSHA Z-2
		С	6 ppm 5 mg/m ³	NIOSH REL
		TWA	3 ppm 2.5 mg/m ³	NIOSH REL
Carbonyl difluoride	353-50-4	TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
		TWA	2 ppm 5 mg/m³	NIOSH REL
		ST	5 ppm 15 mg/m³	NIOSH REL
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m ³	NIOSH REL
		ST	30,000 ppm 54,000 mg/m ³	NIOSH REL
		TWA	5,000 ppm	OSHA Z-1

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 11/02/2023

 1.1
 10/24/2024
 11290755-00002
 Date of first issue: 11/02/2023

			9,000 mg/m ³	
Carbon monoxide	630-08-0	TWA	25 ppm	ACGIH
		TWA	35 ppm 40 mg/m³	NIOSH REL
		С	200 ppm 229 mg/m³	NIOSH REL
		TWA	50 ppm 55 mg/m ³	OSHA Z-1

Engineering measures : Processing may form hazardous compounds (see section

10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous liquid

Color : No data available

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products

Thermal decomposition : Hydrogen fluoride

Carbonyl difluoride Carbon dioxide Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 114.428 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 5000 ppm

Test atmosphere: gas

Method: Cardiac sensitization study

Lowest observed adverse effect concentration (Dog): > 5000

ppm

Test atmosphere: gas

Method: Cardiac sensitization study

Cardiac sensitisation threshold limit (Dog): > 51,544 mg/m³

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

Test atmosphere: gas

Method: Cardiac sensitization study

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Poly(oxy<trifluoro(trifluoromethyl)ethylene>), omega-fluoro-alpha-<tetrafluoro-1 <<(hydroxyphenoxyphosphinyl)oxy>methyl>ethyl>-

.

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Poly(oxy<trifluoro(trifluoromethyl)ethylene>), omega-fluoro-alpha-<tetrafluoro-1 <<(hydroxyphenoxyphosphinyl)oxy>methyl>-

:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Poly(oxy<trifluoro(trifluoromethyl)ethylene>), omega-fluoro-alpha-<tetrafluoro-1 <<(hydroxyphenoxyphosphinyl)oxy>methyl>ethyl>-

:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

Respiratory sensitization

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Test Type : Buehler Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Poly(oxy<trifluoro(trifluoromethyl)ethylene>), omega-fluoro-alpha-<tetrafluoro-1 <<(hydroxyphenoxyphosphinyl)oxy>methyl>-

:

Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Weight of evidence does not support classification as a germ

Assessment

cell mutagen.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 415

Result: negative

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 414

Result: negative

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

STOT-single exposure

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Routes of exposure : Ingestion

Assessment : No significant health effects observed in animals at concentra-

tions of 2000 mg/kg bw or less

Routes of exposure : Skin contact

Assessment : No significant health effects observed in animals at concentra-

tions of 2000 mg/kg bw or less

Routes of exposure : inhalation (vapor)

Assessment : No significant health effects observed in animals at concentra-

tions of 20 mg/l/4h or less

STOT-repeated exposure

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Routes of exposure : inhalation (vapor)

Assessment : No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 10/24/2024 11290755-00002 Date of first issue: 11/02/2023 1.1

Repeated dose toxicity

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Species Rat, male and female

NOAEL 15.463 mg/l LOAEL 20.618 mg/l : inhalation (vapor) Application Route

Exposure time 90 Days

Method : OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Toxicity to fish LC50 (Danio rerio (zebra fish)): 13 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 10.6 mg/l

NOEC (Daphnia magna (Water flea)): 1.72 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Selenastrum capricornutum (green algae)): > 120 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Scenedesmus capricornutum (fresh water algae)): 120

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

Exposure time: 21 d

Method: OECD Test Guideline 211 ic toxicity)

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

Poly(oxy<trifluoro(trifluoromethyl)ethylene>), omega-fluoro-alpha-<tetrafluoro-1 <<(hydroxyphe-noxyphosphinyl)oxy>methyl>-

:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic effects cannot be excluded

Chronic aquatic toxicity : Toxic effects cannot be excluded

Persistence and degradability

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

1,1,1,2,2,3,4,5,5,5-Decafluoropentane:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-

octanol/water

log Pow: 2.4 (75 °F / 24 °C)

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

PFPE fluid Trade secret 1,1,1,2,2,3,4,5,5,5-Decafluoropentane 138495-42-8 Poly(oxy<trifluoro(trifluoromethyl)ethylene>), omega-fluoroalpha-<tetrafluoro-1 <<(hydroxyphenoxyphos-

phinyl)oxy>methyl>ethyl>-

California Prop. 65

WARNING: This product can expose you to chemicals including Pentadecafluorooctanoic acid, which is/are known to the State of California to cause cancer, and Carbon monoxide, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov. Note to User: This product is not made with PFOA nor is PFOA intentionally present in the product; however, it is possible that PFOA may be present as an impurity at background (environmental) levels.

International Regulations

Montreal Protocol : 1,1,1,2,2,3,4,5,5,5-

Decafluoropentane

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

Additional regulatory information

1,1,1,2,2,3,4,5,5,5- 138495-42-8

Decafluoropentane

The United States Environmental Protection Agency (USEPA) has established a Significant New Use Rule (SNUR) for one of the components in this product.


See 40 CFR § 721.5645

This material contains one or more substances which requires export notification under TSCA Section 12(b) and 40 CFR Part 707 Subpart D:

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2 WEEL : Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIH / C : Ceiling limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-2 / TWA : 8-hour time weighted average WEEL / STEL : Short term exposure limit

WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

Data Sheet cy, http://echa.europa.eu/

Revision Date : 10/24/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their

according to the OSHA Hazard Communication Standard



Krytox™ Anti-Rust 4578

Version Revision Date: SDS Number: Date of last issue: 11/02/2023 1.1 10/24/2024 11290755-00002 Date of first issue: 11/02/2023

intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8

Chemours Confidential Business Information



The Chemours Company FC, LLC 1007 Market Street Wilmington, DE 19801 United States of America (USA)

Ref:	130000150962		
Revision date:	12/31/2024		
Version	1.2		

TRI Supplier Notification for Chemicals of Special Concern

Product name: Krytox™ Anti-Rust 4578

This letter is to inform you that the product listed above contains the following Chemical(s) of Special Concern (CSC), which are subject to section 313 of the Emergency Planning and Community Right-to-Know Act (EPCRA). CSC are a subpart listing of chemicals and compounds subject to the Supplier Notification Requirements in 40 C.F.R. 372.45. The chemical(s) listed below are in compliance with TSCA and may not be intentionally present in the product; however, it is possible that these chemical(s) may be present as an impurity and the exact concentration may vary between batches.

Chemical name	CAS No.	Value	Unit	Test Method
Perfluorobutanoic acid	375-22-4	< 4	PPB	Chemours Extraction SOP*

^{*}Chemours SOP for Extraction of Residuals from Fluoropolymer Matrices. https://www.chemours.com/en/-/media/files/corporate/sop-residual-extractions-from-fluoropolymer-matrices.pdf

The data above is based on the best readily available information as of the date of this letter, which may include representative samples of products. This information is supplemental to safety and regulatory information provided on the SDS. The content of this letter is confidential and intended for the recipient to use for regulatory purposes only.

Please note that if you repackage or otherwise redistribute this product to certain industrial customers as per 40 CFR 372.45(a)(3)(ii), a notice similar to this one should be sent to those customers.

If you have any questions or concerns, please reach out to your account manager.

Disclaimer:

This information is given in good faith and is based on data we believe to be reliable on our current level of knowledge as of the date of this response. The information applies only to the specific material designated herein as sold by Chemours and does not apply to use in any process or in combination with any other material. Since conditions of use and applications of above-mentioned products are outside Chemours' control, Chemours makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information. Please note that we do not routinely analyze our products for non-intentionally added substances, unless required for regulatory compliance purposes.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.