according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

SECTION 1. IDENTIFICATION

Product name : Opteon™ SF10 Specialty Fluid

Product code : D15439432

SDS-Identcode : 130000143912

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent

Carrier fluid Heat transfer fluids

Restrictions on use : For professional users only., Do not use product for anything

outside of the above specified uses

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

Other hazards

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Substance name : Methoxytridecafluoroheptene isomers

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 04/16/2025 1624938-00023 Date of first issue: 05/15/2017 6.0

CAS-No. Not Assigned

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Methoxytridecafluorohep- tene isomers	-	>= 80 - <= 100	TSC

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact Wash with water and soap as a precaution.

Get medical attention if symptoms occur.

In case of eye contact Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

and effects, both acute and

delayed

Inhalation may provoke the following symptoms:

Dizziness

May cause cardiac arrhythmia.

Protection of first-aiders No special precautions are necessary for first aid responders.

Notes to physician Because of possible disturbances of cardiac rhythm, ca-

techolamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with spe-

cial caution.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Hydrogen fluoride carbonyl fluoride

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Carbon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus for firefighting if

necessary.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions :

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety

practice, based on the results of the workplace exposure as-

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Do not expose drums to direct heat or temperature above

46°C (115°F) to avoid pressurizing and possibly distorting the

drums.

Material should not be dispensed by pouring from pail/drum shipping containers containing 5 gallons or more. The use of a drum pump is recommended for dispensing from pail/drum shipping containers with 5 gallons or more, except for smaller containers where adequate ventilation can be used to manage

the exposure.

Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage tem-

perature

< 115 °F / < 46 °C

Further information on stor-

age stability

Keep away from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methoxytridecafluoroheptene isomers	Not Assigned	TWA	200 ppm	WEEL

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear, colorless

Odor : mild

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : $< -121 \, ^{\circ}\text{F} \, / < -85 \, ^{\circ}\text{C}$

Initial boiling point and boiling :

range

230.9 °F / 110.5 °C

Flash point : does not flash

Evaporation rate : 2.2

(Butyl Acetate=1.0)

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

Upper explosion limit / Upper

flammability limit

Upper flammability limit

Method: ASTM E681

None.

Lower explosion limit / Lower

flammability limit

Lower flammability limit

Method: ASTM E681

None.

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Vapor pressure : 21.5 hPa (68 °F / 20 °C)

28.8 hPa (77 °F / 25 °C)

Relative vapor density : 12.1

(Air = 1.0)

Relative density : 1.59 (77 °F / 25 °C)

Solubility(ies)

Water solubility : 0.00015 g/l slightly soluble (75 °F / 24 °C)

Partition coefficient: n-

octanol/water

: log Pow: 4.4 - 4.9 (77 °F / 25 °C)

Autoignition temperature : 658 - 664 °F / 348 - 351 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : 0.74 mm²/s (77 °F / 25 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): > 222.15 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Method : OECD Test Guideline 429

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Components:

Methoxytridecafluoroheptene isomers:

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

STOT-single exposure

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

Routes of exposure : Ingestion

Assessment : No significant health effects observed in animals at concentra-

tions of 2000 mg/kg bw or less

Routes of exposure : Skin contact

Assessment : No significant health effects observed in animals at concentra-

tions of 2000 mg/kg bw or less

Routes of exposure : inhalation (vapor)

Assessment : No significant health effects observed in animals at concentra-

tions of 20 mg/l/4h or less

STOT-repeated exposure

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

Routes of exposure : Ingestion

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Routes of exposure : inhalation (vapor)

Assessment : No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Methoxytridecafluoroheptene isomers:

Species : Rat, male and female

NOAEL : 1,000 mg/kg
LOAEL : > 1,000 mg/kg
Application Route : Ingestion

Exposure time : 90 d

Method : OECD Test Guideline 408

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Species : Rat, male and female

NOAEL : 37.025 mg/l
LOAEL : 75.531 mg/l
Application Route : inhalation (vapor)

Exposure time : 28 d

Method : OECD Test Guideline 412

Aspiration toxicity

Not classified based on available information.

Components:

Methoxytridecafluoroheptene isomers:

No aspiration toxicity classification

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Methoxytridecafluoroheptene isomers:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 0.096 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other:

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 0.157 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

: ErC50 (Pseudokirchneriella subcapitata (green algae)): >

0.000477 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

NOEC (Pseudokirchneriella subcapitata (green algae)):

0.000477 mg/l Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.107 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: No toxicity at the limit of solubility.

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Persistence and degradability

Components:

Methoxytridecafluoroheptene isomers:

Biodegradability : Result: Not inherently biodegradable.

Method: OECD Test Guideline 302C

Bioaccumulative potential

Components:

Methoxytridecafluoroheptene isomers:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 1,990 Method: OECD Test Guideline 305

Mobility in soil

Components:

Methoxytridecafluoroheptene isomers:

Distribution among environ- :

mental compartments

log Koc: 4.5

Remarks: immobile

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Methoxytridecafluoroheptene isomers Not Assigned

SECTION 16. OTHER INFORMATION

Further information


according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

WEEL : Workplace Environmental Exposure Levels (WEEL)

WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials: bw - Body weight: CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic sub-

according to the OSHA Hazard Communication Standard



Opteon™ SF10 Specialty Fluid

Version Revision Date: SDS Number: Date of last issue: 10/17/2024 6.0 04/16/2025 1624938-00023 Date of first issue: 05/15/2017

stance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 04/16/2025

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8