

MS-752U Ultra Pure Specialty Fluid

Description:

Cleaning oxygen service parts is more critical than most other cleaning applications. Particles or residue left behind may hinder the operation of valves, sensors, or controls, causing excessive friction that may lead to potential ignition or explosion. MS-752U is an Ultra Pure grade of a Vertrel™ Cleaning Agent. Purified by Miller-Stephenson's proprietary processes, our MS-752U contains sub-ppm levels of NVR. Optimized for use as a final rinse of parts in ultra-critical application. This product also can be used for precision and specialty applications in many industries such as Electronics, Military, Aerospace, and Communications. It is ideally suited for removing mineral oil, vacuum oil, wax, heavy grease, cutting oil, stamping oil, hydraulic oil, and gear oil.

Advantages:

- Evaporates quickly; Leaves no residue.
- < 1.0 ppm particulate and NVR levels
- Utilized by major gas and aerospace manufacturers.
- Nonflammable, Non-ozone depleting
- Compatible with most plastics, elastomers, and metals
- RoHS2 & RoHS3 compliant

Properties of Solvent:

Boiling Point	102°F/39°C
Liquid Density	1.41 g/cc
Vapor Pressure	464 mmHg
Surface Tension	15.2 dyn/cm
Viscosity	0.49 cP
VOC Content	536 g/l

Plastic Compatibility:

(Immersion: 15 minutes at Room Temperature)

- | | |
|-----------------------|--------------------------|
| • Acetal | • Polypropylene |
| • PEK, PEEK | • Polyimides |
| • PTFE, ETFE | • Polyethylene |
| • Polyester, PBT, PET | • Epoxy-Phenolics |
| • Polyvinylchloride | • Liquid Crystal Polymer |

NOTE: Acrylic, ABS, and polycarbonate, if under stress, may show slight cracking or crazing damage. Test for compatibility before use.

Elastomer Compatibility:

(Immersion: 1 week at 39°C/102°F)

- | | |
|-----------------------------|---------------|
| • Butyl Rubber ¹ | • Polysulfide |
| • Neoprene ¹ | • EPDM |
| • Chlorosulfonated PE | |

¹ Swelling with low extractables.

Note: Elastomer swelling and shrinking will, in most cases, revert to within a few percent of original size after air drying. Swell, shrinkage, and extractables are strongly affected by the compounding agents, plasticizers, and curing used in the manufacture of the elastomers. Test for compatibility before use.

Metal Compatibility:

(Immersion: 2 weeks at 248°F/120°C)

- Aluminum
- Copper
- Iron

Purity Specifications:

Properties	Unit	Specifications
Vertrel™ XF	wt%	62.0 ± 1.0
Trans-1,2-dichloroethylene	wt%	38.0 ± 1.0
Specific Gravity	g/mL	1.41
pH		6.5 – 7.2
Total Purity	wt%	99.999 min
Non-Volatile Residue	ppm, wt	≤1.0 ppm
Particle Count	mg/L	0.00
Moisture	ppm wt	75 ppm max
Acidity (as HCl)	ppm wt	1.0 max
Appearance		Clear, colorless

Safety Data Sheet (SDS) is available upon request.

Vertrel™ is a trademark of The Chemours Company FC, LLC.

LIMITATION OF LIABILITY AND REMEDIES: Manufacturer warrants that, at the time of shipment by the Manufacturer, this product is free from defect in material and manufacture. If the product is proved to be defective, the exclusive remedy, at Manufacturer's option, shall be refund of the purchase price or replacement of the defective product, provided written notice of the defect is given no later than one year after the date of shipment by the Manufacturer. Manufacturer shall not otherwise be liable for loss or damages whether direct, indirect, incidental or consequential, regardless of the legal theory asserted, including negligence and strict liability. **Manufacturer expressly disclaims all implied warranties, including the implied warranty of merchantability and the implied warranty of fitness for a particular purpose. There are no warranties which extend beyond the description on the face hereof.**

1537-9R